PL H 8W HYBM TITANIUM LED SERIES









- HYBrid installation DIRect or BYPass
- Compatible with magnetic ballasts DIRect installation
- Built-in universal voltage driver Bypass installation
- Compatible with G24d, GX24d, G24q & GX24q bases
- Exceptional efficacy 119 LPW
- Lasts 4 times longer than CFL

















PL PRODUCT FEATURES

BYPass Installation - Electronic Ballasts

This PL H lamp is not compatible with electronic ballasts and requires bypassing the ballast during installation. The lamp runs directly off line voltage to eliminate compatibility problems, incidental power loss, lifetime issues, and maintenance costs associated with ballasts.




HYBrid Installation - DIRect or BYPass - Magnetic Ballasts





When used with a magnetic ballast, the PL H can function as a plug & play lamp and operate with the existing ballast. If the ballast is not compatible, it can be bypassed and the lamp can run directly off line voltage.

PL H 8W HYBM TITANIUM LED SERIES










G24d, GX24d, G24q & GX24q (2/4-pin CFL) Base:

Voltage: Magnetic ballast compatible

120-277V

Dimmable: No PF: 0.9

Lifetime (L70): 50,000 hrs Weight: 0.18lb / 82g



SPECIFICATIONS

Model	Product	Power (W)	сст	CRI (typ.)	Lumens	LPW	Beam Angle
8PLH/827/HYBM	98399	8	Soft White 2700K	82	870	109	110°
8PLH/830/HYBM	98400	8	Warm White 3000K	82	920	115	110°
8PLH/835/HYBM	98401	8	Neutral White 3500K	82	920	115	110°
8PLH/840/HYBM	98402	8	Cool White 4000K	82	950	119	(110°

Suitable for damp locations. Not for use where directly exposed to weather or water