

ProLED GU24 A19 Omnidirectional Series







ProLED[®] GU24 Omnidirectional A-Shape Series lamps offer an economical and even more energy efficient alternative to non-dimmable compact fluorescent lamps





Omnidirectional Optical Design Provides 230° Light Distribution

UL Listed for Damp Location & Enclosed Luminaires

ENERGY STAR® Certified

Backed by a 3-Year Warranty

Applications: Home Education Hospitality

Retail

Markets: Residential Commercial

Contact Your Customer Care Specialist For Pricing, Orders And Technical Support.

ProLED. **GU24 A19 Omnidirectional Series**

Specifications

- 3-year warranty

- Non-Dimmable


- Rated for ICAT fixtures

- Available in 2700K, 3000K, 4000K or 5000K CCT

- UL Listed for damp location and enclosed luminaires

- 230° degree beam angle creates uniform distribution of light

Savings Comparison



^v Maintenance costs based on 15 minutes at \$40 per/hr ¥ Energy costs based on \$0.11 kWh



	2.36"
	(60mm)
4.33" (109mm)	GU24 A19

0.00

Ordering Information

	Watts	Base	Product #	Product Code	Volts	Color Temp.	CRI	Lumens	Useful Life*	Beam Angle	Pkg. Qty.	MOL	Equivalent CFL Wattage
0	3/9/12	Medium	83191	A19FR3/9/12/830/3-WAY/LED	120	3000K	82	280/950/1200	15,000	220°	1/6	4.646	30/70/100
0	9.5	GU24	83180	A19FR9/827/OMNI2/GU24/LED	120	2700K	82	800	15,000	220°	1/6	4.331	60
0	9.5	GU24	83181	A19FR9/830/OMNI2/GU24/LED	120	3000K	82	800	15,000	<mark>220°</mark>	1/6	4.331	60
0	9.5	GU24	83182	A19FR9/840/OMNI2/GU24/LED	120	4000K	82	800	15,000	220°	1/6	4.331	60
0	9.5	GU24	83183	A19FR9/850/OMNI2/GU24/LED	120	5000K	82	800	15,000	220°	1/6	4.331	60
0	11.5	GU24	83184	A19FR11/827/OMNI2/GU24/LED	120	2700K	82	1100	15,000	220°	1/6	4.331	75
0	15.5	GU24	83189	A19FR15/840/OMNI2/GU24/LED	120	4000K	82	1600	15,000	220°	1/6	4.331	100

• NEW ITEM! * Useful Life is defined as the point in time at which the lamp will maintain at least 70% of its initial lumens. The lamp will continue to burn past this point, but at decreased light levels.

Maranty – Commercial / Industrial: This product is warranted for 3 years from the date of purchase. 15,000 hour useful life rating is based on a maximum ambient temperature of 45°C. Exceeding this ambient temperature rating may result in reduced life.

©2018 Halco Lighting Technologies, LLC. All rights reserved. Halco and ProLED are registered trademarks of Halco Lighting Technologies. All sizes and specifications are subject to change. 08-08-18. Re-order #9117