



GE  
Lighting

68921 - F32T8/SPX35/U6/2

F32T8/SPX35/U6/2

Product Photo



#### GENERAL CHARACTERISTICS

Base Description	Medium Bi-Pin
Base Type	Pin/Plug-In
Mercury Content	90 mg
Mercury-Picogram per mean lm hr	1711
Rated Life Rapid Start - Hrs	20000 h @ 3 h
Starting Temp (MIN) C-degrees	10 °C
Bulb Material	Sodalime glass
Rated Life Hours-nominal	20000 h
Primary Application	Full Wattage
Product Technology	Linear Fluorescent
Base	G13
Bulb Shape	T8

#### PHOTOMETRIC CHARACTERISTICS

Mean Lumens nominal	2465 lm
Nominal Initial Lumen per Watt	85
Initial Lumens-nominal	2800 lm
Color Rendering Index-CRI	82
Color Temperature	3500 K

#### PRODUCT INFORMATION

Product Code	68921
Description	F32T8/SPX35/U6/2
Alternative Unit Of Measure	CASE
Standard Package Quantity	
Ean UPC	043168689212
Standard Package GTIN	10043168689219
No Of Items Per Sales Unit	
No Of Items Per Standard Package	
Sales Unit	Case
UCC	043168689212

#### DIMENSIONS

Diameter	1.0 in
Nominal Length	22.5 in

#### ELECTRICAL CHARACTERISTICS

Rated power (Watts)	32 W
---------------------	------