



S29913

14T8/LED/48-830/BP 120-277V
 14 watt T8 LED; Medium bi-pin base; 3000K; 50000 Average
 rated hours; 1700 lumens

Features

- All glass tube
- Approved for use with tube guards
- Direct wire 120-277V line voltage*
- NSF Approved
- No ballast or external driver required
- Built-in shock resistant circuit - (not hot until both ends are installed)



S29913

*Existing wiring to both sockets can remain in place

*Will work on both shunted or non-shunted sockets

| Item Number | UPC | Voltage | Watts | Operating Frequency | Fluorescent Equivalent | Lamp Shape | Base |
|-------------|--------------|---------|-------|---------------------|------------------------|------------|---------------|
| S29913 | 045923299131 | 120-277 | 14 | 50/60Hz | 25W-32W | T8 | Medium Bi-Pin |

| ANSI Base | Lamp Code | Dimmable/Non-Dimmable | Finish | MOL In Inches | MOD In Inches | Initial Lumens | Average Rated Hours |
|-----------|-----------------------------|-----------------------|--------|---------------|---------------|----------------|---------------------|
| G13 | 14T8/LED/48-830/BP 120-277V | Non-Dimmable | White | 48" | 1.00" | 1700 | 50000 |

| Kelvin Temp | Color | CRI | Beam Spread Deg | Pack | Package Type | CEC Status | DLC ID: |
|-------------|---------------|-----|-----------------|------|--------------|----------------------------|--|
| 3000 | Halogen White | 82 | 210 | 25 | Box | Does not meet requirements | PLIKTNJJHGHR DLC Search |

| RoHS Compliant | UL or ETL Listed | UL Classification | Warranty |
|----------------|------------------|--|-----------------|
| Yes | Yes | cULus Classified - Damp Location Rated | 5-Year Warranty |