



S29929

12T8/LED/36-850/BP 120-277V
 12 watt T8 LED; Medium bi-pin base; 5000K; 50000 Average
 rated hours; 1450 lumens

Features

- All glass tube
- Approved for use with tube guards
- Direct wire 120-277V line voltage*
- NSF Approved
- No ballast or external driver required
- Built-in shock resistant circuit - (not hot until both ends are installed)



S29929

*Existing wiring to both sockets can remain in place

*Will work on both shunted or non-shunted sockets

Item Number	UPC	Voltage	Watts	Operating Frequency	Fluorescent Equivalent	Lamp Shape	Base	
S29929	045923299292	120-277	12	50/60Hz	25W	T8	Medium Bi-Pin	
ANSI Base	Lamp Code	Dimmable/Non-Dimmable		Finish	MOL In Inches	MOD In Inches	Initial Lumens	Average Rated Hours
G13	12T8/LED/36-850/BP 120-277V	Non-Dimmable		White	36"	1.00"	1450	50000
Kelvin Temp	Color	CRI	Beam Spread Deg	Operating Temperature		Pack	Package Type	CEC Status
5000	Daylight White	82	210	-20C (-4F) to a maximum of +45C (+113F)		25	Box	Does not meet requirements
DLC ID:		RoHS Compliant	UL or ETL Listed	UL Classification			Warranty	
PLCM6AAFCP4G		Yes	Yes	cULus Classified - Damp Location Rated			5 Year Limited	