



# LED U6 SERIES


## BYPass LED U6 - FB34

### COMMERCIAL SPEC GRADE

Replaces 32W FB34 Fluorescent U6



#### Superior All-Around Light Distribution



#### Shatter-Resistant



Designed for high efficiency and versatility, the IC-Driver allows for exceptional BYPass performance

Seamless output from end-to-end, Light Engine allows for fully uniform light output.



### FEATURES

- Easy BYPass the Ballast for Easy Installation
- Universal Input Voltage - 120-277V
- Uniform Light Output From End-to-End
- Instant-ON with No Flicker
- 5-Year Warranty
- DLC 4.1 Listed
- UL Listed

### Specifications and Technical (U6 | BYPass)


MODEL	BASE TYPE	WATTS / EQV.	LUMEN	CCT	DIMENSION	VOLTAGE	CRI	THD	CARTON QTY	LIGHT DISTRIBUTION
LBU6B16301	Bi-Pin G13	16W / 32W	2100LM	3000K	6.0" x 22.5"	120-277V	83	<20%	16	310°
LBU6B16351	Bi-Pin G13	16W / 32W	2100LM	3500K	6.0" x 22.5"	120-277V	83	<20%	16	310°
LBU6B16411	Bi-Pin G13	16W / 32W	2100LM	4100K	6.0" x 22.5"	120-277V	83	<20%	16	310°
LBU6B16501	Bi-Pin G13	16W / 32W	2100LM	5000K	6.0" x 22.5"	120-277V	83	<20%	16	310°

\* Suitable for use in totally enclosed fixtures

\*\* Suitable for damp locations. Not for use where exposed to the weather or moisture

\*\*\* See Installation Instructions PDF for installation instructions

### Installation Configuration



BYPass

### Light Distribution Curve

