



FEATURES

- Meets DLC performance and efficiency criteria
- 3500 Kelvin color matched for halogen bulbs
- Equivalent to a 32-Watt fluorescent U-Bend
- Frosted glass lens evenly diffuses light
- UL listed for use in damp locations
- DLC® Part Number: PLTSP14213
- Bi-Pin G13 base

APPLICATIONS

- Office spaces and conference rooms
- Classrooms and hallways
- Hospitals and lobbies

❖ For use with non-shunted sockets only



SKU#	Kelvin	Lumens	CRI	Wattage	Voltage	DLC?	Base	Life Hours	Warranty
LEDT-10068CS	3500	2100	82	18	120-277	YES	Bi-Pin	50,000	5 Year

SPECIFICATIONS

DIMMABLE	NO LUMENS	2,100
DLC LISTED	YES VOLTAGE	120-277
SAFETY RATING	UL DAMP LENS	FROSTED GLASS
CRI	82 LEG SPACING	6 INCH
COLOR	HALOGEN WHITE BALLAST TYPE	BALLAST BYPASS
COLOR TEMPERATURE	3500K DIAMETER	8.02 IN.
LIFE HOURS	50,000 LENGTH	22.425 IN.
WATTAGE	18 WATTS FLUORESCENT EQUAL.....	32 WATT