



# S29904

17T8/LED/48-830/BP 120-277V  
 17 watt T8 LED; 3000K; Medium Bi Pin base; 50000 Average  
 rated hours; 2100 Lumens

## Features

- All glass tube
- Direct wire 120-277V line voltage\*
- NSF/ANSI Standard 2 Approved
- No ballast or external driver required
- Built-in shock resistant circuit - (not hot until both ends are installed)



S29904

\*Existing wiring to both sockets can remain in place  
 \*Will work on both shunted or non-shunted sockets



Item Number	UPC	Voltage	Watts	Operating Frequency	Fluorescent Equivalent	Lamp Shape	Base
S29904	045923299049	120-277	17	50/60Hz	32W	T8	Medium Bi-Pin
ANSI Base	Lamp Code	Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches	Initial Lumens	Average Rated Hours
G13	17T8/LED/48-830/BP 120-277V	Non-Dimmable	White	48"	1.00"	2100	50000
Kelvin Temp	Color	CRI	Beam Spread Deg	Operating Temperature	Pack	CEC Status	RoHS Compliant
3000	Soft White	82	210	-20C (-4F) to a maximum of +45C (+113F)	10	Lawful for sale in California	Yes
UL or ETL Listed		UL Classification				Warranty	
Yes		cULus Classified - Damp Location Rated				5 Year Limited	