

# SORAA

## Electrical compatibility – BRILLIANT HL PAR20 8.5W & 10.8W 120V lamps - North America

### Table of contents

- General compatibility guidelines.....Page 2
- Dimming compatibility.....Page 3-4

## General compatibility guidelines

### Scope

This document provides the basic guidelines regards electrical compatibility of SORAA Brilliant HL 120V PAR20 lamps and compatibility tables.

### Dimmer Compatibility

SORAA Brilliant HL 120V PAR20 lamps are made to work with trailing edge (reverse phase) and leading edge (forward phase) phase cut dimmers. However, the use of trailing edge dimmers is preferred and will show in general better behavior .

Dimmer compatibility tables are available on this document.

The percentages for each dimmer combination are the percentage of light output that we were able to dim down to without seeing any problems like flicker/shimmer. Anything 30% or above is considered not compatible and you will see a “NC” in a grey cell.

There might be a minimum wattage load on the dimmer. If this minimum load is not met, there might be compatibility issues.

### Maximum number of lamps on a dimmer

The following need to be considered when determining the amount of lamps on a dimmer.

1. SORAA tests have been carried out with 1 lamp unless stated otherwise.
2. There is a repetitive, very brief current spike the LED lamp will see twice per cycle. This current spike has to be provided by the dimmer, and will affect the recommended lamp load on each dimmer.
3. Ultimately the dimmer manufacturer is the only one with authority to rate their product, but SORAA can give an Engineering estimate.
4. We recommend to use a 5.0 de-rating factor for incandescent/halogen dimmers loaded with our 120V lamps.

**For example for a 500W dimmer it would mean  $500/5 = 100W$  of LED, so an estimated maximum of 9 lamps 11W.**

### Disclaimer

Compatibility tests are conducted by Soraa only as guidance for the user.

All tests are conducted under bench conditions; results may differ from test results depending on conditions at the application site.

Results may vary due to variability in component choices and manufacturing processes by the transformer and dimmer manufacturers.

For more information on the dimmers/transformers, please find specs on the manufacturer’s website.

**SORAA BRILLIANT HL PAR20 120V 8.5W & 10.8W - DIMMER COMPATIBILITY LIST - North America**

<b>Dimmer Manufacturer</b>	<b>Dimmer family</b>	<b>Dimmer Model</b>	<b>Dimming phase</b>	<b>Number of lamps per dimmer tested</b>	<b>Dim (%)</b>	<b>Comments</b>
<b>Creston</b>		DIN-1DIMU4	Reverse	3	0%	
<b>Lutron</b>	Caseta	PD-5NE	Reverse	3	7%	
<b>Lutron</b>	Diva	DVCL-153P	Forward	3	5%	
<b>Lutron</b>	Diva	DVELV-300P	Reverse	3	4%	
<b>Lutron</b>	Diva	DVLV-600P	Forward	3	11%	
<b>Lutron</b>	Grafik Eye QS	QSGRJ-3P	Forward	3	1%	
<b>Lutron</b>	Interface	PHPM with Grafik Eye QS	Reverse	3	1%	
<b>Lutron</b>	Maestro	MACL-153M	Forward	3	12%	
<b>Lutron</b>	Radio Ra2	RRD-6NA	Reverse	3	1%	
<b>Lutron</b>	Remote Power Modules / Homeworks	HW / LP-RPM-4A-120	Reverse	3	0%	
<b>Lutron</b>	Skylark	SLV-600P	Forward	3	9%	
<b>Lutron</b>	Skylark	SELV-300P	Reverse	3	4%	
<b>Marlin</b>	Stellar RMS 4	Stellar RMS 4	Reverse	3	1%	

**Notes:**

Compatibility tests are conducted by Soraal (unless stated otherwise) only as guidance for the user

All tests are conducted under bench conditions; results may differ from test results depending on conditions at the application site

Results may vary due to variability in component choices and manufacturing processes by the dimmer manufacturer

Regards compatibility tests conducted by dimmer manufacturer, please contact Soraal or the manufacturer for more details and/or reports.

(\*) Test results with this dimmer added to the compatibility list as of this Revision

--%	Dims to < 20% (of the measured light output)
--%	Dims to 20-30% (of the measured light output)
NC	Not compatible (or dims to >30%)
Blank cell	Not tested