



S16502

FC8T9/LED/CIR/865/BP
 LED Circline; 11 Watt; T9; 6500K; G10Q Base; 120-277 volts;
 Ballast Bypass



S16502

Features

- No ballast or external driver required
- Replaces 22W fluorescent Circlines
- Direct wire 120-277V line voltage*
- NSF/ANSI Approved

Item Number	UPC	Voltage	Watts	Operating Frequency	Fluorescent Equivalent	Power Factor	Lamp Shape
S16502	045923165023	120-277	11	50/60Hz	22W	0.90	T9
Base	ANSI Base	Lamp Code	Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches	Initial Lumens
Medium Bi-Pin	G10q	FC8T9/LED/CIR/865/BP	Non-Dimmable	White	1"	8.00"	1210
Average Rated Hours	Kelvin Temp	Color	CRI	Beam Spread Deg	Operating Temperature	THD	Pack
50000	6500	Daylight	80	135	-25C (-13F) to a maximum of +45C (+113F)		12/1
Package Type	Material	RoHS Compliant	UL or ETL Listed	ETL Classification	Warranty		
Box	Plastic	Yes	Yes	cETLus - Damp Location Rated	5 Year Limited		