



LED Recessed Retrofits

DIMMABLE • 35,000 HOURS • EASY INSTALLATION

TCP's Dimmable Retrofit Kits are the perfect choice for new construction and retrofit opportunities when a sleek, integrated look is preferred.

LIMITLESS OPTIONS FOR THE FOLLOWING APPLICATIONS

- Commercial
- Industrial
- Retail
- Residential
- Healthcare

FEATURES

- Long life: 35,000 hours
- Very low heat generation
- Excellent color consistency and CRI
- Mounts directly to recessed can: 4 or 5/6 inch
- Shatter resistant
- Smooth, uniform dimming from 100 - 5%

BENEFITS

- Minimizes replacement and maintenance costs
- Perfect for sensitive display lighting such as art galleries
- Enhances colors of focal point while maintaining uniformity throughout lighting installation from lamp to lamp
- Easy installation and integrated trim Pigtail and spring clips
- Lower the risk of injury and breakage

SPECIFICATIONS

Color Temperatures..... 2700K, 3000K, 3500K, 4100K, 5000K
 Wattage options 14W, 11W, 10W, 9W
 Input Line Voltage 120 VAC
 Input Line Frequency..... 50/60HZ
 Lamp Life (Rated) 35,000 hours
 Minimum Starting Temp -22F/-30C
 Maximum Operating Temp..... 40°C
 CRI..... 80, 90

IC-rated for direct contact with insulation

UL approved for damp location (indoor only)—outdoor environment may cause yellowing of the white trim. This is not covered by warranty.



5 YEAR WARRANTY

*Based on 12 hours use per day



RoHS COMPLIANT



LED
we know light.™





LED RECESSED RETROFITS

DIMMABLE • 35,000 HOURS • EASY INSTALLATION

ITEM #	DESCRIPTION	ENERGY STAR V2.1	VOLTAGE	LED WATTS	REPLACEMENT	LUMENS	LPW	CRI	COLOR TEMP	MOL (inches)	DIA (inches)	CASE QUANTITY
--------	-------------	------------------	---------	-----------	-------------	--------	-----	-----	------------	--------------	--------------	---------------

5/6" Recessed Retrofits

120 Watt Replacement • 35,000 Hour

LED14DR5627K	LED 5/6" 12W DIM 120W EQ - 2700K	★	120V	12	120	1250	89.3	80	2700K	3.0	7.4	6
LED14DR5630K	LED 5/6" 12W DIM 120W EQ - 3000K	★	120V	12	120	1300	92.9	80	3000K	3.0	7.4	6
LED14DR5641K	LED 5/6" 12W DIM 120W EQ - 4100K	★	120V	12	120	1300	92.9	80	4100K	3.0	7.4	6
LED14DR5650K	LED 5/6" 12W DIM 120W EQ - 5000K	★	120V	12	120	1350	96.4	80	5000K	3.0	7.4	6

75 Watt Replacement • 35,000 Hour

LED11DR5627K	LED 5/6" 9.5W DIM 75W EQ - 2700K	★	120V	9.5	75	850	72.7	80	2700K	3.0	7.4	6
LED11DR5630K	LED 5/6" 9.5W DIM 75W EQ - 3000K	★	120V	9.5	75	850	77.3	80	3000K	3.0	7.4	6
LED11DR5641K	LED 5/6" 9.5W DIM 75W EQ - 4100K	★	120V	9.5	75	875	81.8	80	4100K	3.0	7.4	6
LED11DR5650K	LED 5/6" 9.5W DIM 75W EQ - 5000K	★	120V	9.5	75	900	86.4	80	5000K	3.0	7.4	6

HiCRI • 65 Watt Replacement • 35,000 Hour

L11DR56D3527K95**	LED 5/6" 11W HiCRI DIM 65W EQ - 2700K	★	120V	11	65	700	63.6	90	2700K	3.125	7.4	6
L11DR56D3530K95**	LED 5/6" 11W HiCRI DIM 65W EQ - 3000K	★	120V	11	65	750	86.2	90	3000K	3.125	7.4	6

4" Recessed Retrofits

75 Watt Replacement • 35,000 Hour

LED10DR427K	LED 4" 10W DIM 75W EQ - 2700K	★	120V	10	75	750	75.0	80	2700K	3.0	5.0	6
LED10DR430K	LED 4" 10W DIM 75W EQ - 3000K	★	120V	10	75	750	75.0	80	3000K	3.0	5.0	6
LED10DR435K	LED 4" 10W DIM 75W EQ - 3500K		120V	10	75	620	62.0	80	3500K	3.0	5.0	6
LED10DR441K	LED 4" 10W DIM 75W EQ - 4100K	★	120V	10	75	800	80.0	80	4100K	3.0	5.0	6
LED10DR450K	LED 4" 10W DIM 75W EQ - 5000K	★	120V	10	75	800	80.0	80	5000K	3.0	5.0	6

HiCRI • 50 Watt Replacement • 35,000 Hour

L9DR4D3527K95**	LED 4" 9W HiCRI DIM 50W EQ - 2700K		120V	9	50	550	61.1	90	2700K	3.0	5.2	6
L9DR4D3530K95**	LED 4" 9W HiCRI DIM 50W EQ - 3000K		120V	9	50	550	61.1	90	3000K	3.0	5.2	6

* JA8 Compliant
+ All Plastic Body



*Based on 12 hours use per day

For the most up-to-date specs, please visit www.tcpi.com

TCP®

325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | tcpi.com

©TCP DEC 2018/WF134835

