



## FEATURES

- Meets DLC performance and efficiency criteria
- 5000 Kelvin Daylight White Color Temperature
- Equivalent to a 32-Watt fluorescent U-Bend
- DLC® No. PLTSP14215
- Frosted glass lens evenly diffuses light
- UL listed for use in damp locations
- Bi-Pin G13 base

## APPLICATIONS

- Office spaces and conference rooms
- Classrooms and hallways
- Hospitals and lobbies

❖ For use with non-shunted sockets only



SKU#	Kelvin	Lumens	CRI	Wattage	Voltage	DLC?	Base	Life Hours	Warranty
LEDT-10070CS	5000	2200	82	18	120-277	YES	Bi-Pin	50,000	5 Year

## SPECIFICATIONS

DIMMABLE .....	NO LUMENS .....	2,200
DLC LISTED .....	YES VOLTAGE .....	120-277
SAFETY RATING .....	UL DAMP LENS .....	FROSTED GLASS
CRI .....	82 LEG SPACING .....	6 INCH
COLOR .....	DAYLIGHT WHITE BALLAST TYPE .....	BALLAST BYPASS
COLOR TEMPERATURE .....	5000K DIAMETER .....	8.02 IN.
LIFE HOURS .....	50,000 LENGTH .....	22.425 IN.
WATTAGE .....	18 WATTS FLUORESCENT EQUAL.....	32 WATT