

# LED

## 4 ft. Single-Ended T8 Tube



### FEATURES

- 5000 Kelvin Daylight white color temperature
- Meets DLC performance and efficiency criteria
- Equivalent to a 32-Watt fluorescent T8 tube
- Frosted glass lens evenly diffuses light
- Compatible with non-shunted sockets
- UL listed for use in damp locations
- Bi-Pin G13 base
- DLC® Part Number: PLTSP39215
- NSF /ANSI standard 2 coating

### APPLICATIONS

- Office spaces and work environments
- Kitchens and bathrooms
- Security areas and basements



SKU#	Kelvin	Lumens	CRI	Wattage	Voltage	DLC?	Base	LED L70 Life Hours	Warranty
PLT-90032	5000	1800	82	15	120-277	YES	Bi-Pin	≥100,000	5 Years

### SPECIFICATIONS

DIMMABLE	NO	LUMENS	1,800
DLC LISTED	YES	VOLTAGE	120-277
SAFETY RATING	UL DAMP	LENS	FROSTED GLASS
CRI	82	BASE TYPE	G13
COLOR	DAYLIGHT WHITE	BALLAST TYPE	BALLAST BYPASS
COLOR TEMPERATURE	5000K	DIAMETER	1 IN.
LED L70 LIFE HOURS	≥100,000	LENGTH	48 IN.
WATTAGE	15 WATTS	FLUORESCENT EQUAL	32 WATT