

LED

2 ft. Single-Ended T8 Tube



FEATURES

- Suitable replacement for 17-Watt T8 and 20-Watt T12 fluorescent tubes
- NSF shatterproof coating ensures occupant safety
- Works with non-shunted lampholders
- UL listed for damp locations
- Has a Bi-Pin G13 base
- DLC® Part Number: PLTSP4A213

TYPICAL APPLICATIONS

- Office spaces and conference rooms
- Classrooms and hallways
- Hospitals and lobbies



SKU#	Size	Lumens	Wattage	Kelvin	Operation	CRI	DLC?	Base	Warranty
PLT-90001	2 ft.	1100	9W	3500K	Ballast Bypass	80	Yes	Medium Bi-Pin	5 Year

SPECIFICATIONS

BULB SHAPE	T8	FLUORESCENT EQUAL	17-WATT
DIMMABLE	NO	COMPATIBILITY	BALLAST BYPASS
SAFETY RATING	UL DAMP	LAMPHOLDER(S)	NON-SHUNTED
COLOR	HALOGEN WHITE	LENS	FROSTED GLASS
LIFE HOURS	50,000	LENGTH	24 IN.
LUMENS PER WATT	122	DIAMETER	1 IN.
VOLTAGE	120-277		