

# LED 4 ft. Single-Ended T8 Tube

PLT  
&  
T



## FEATURES

- Compatible with non-shunted sockets
- Meets DLC performance and efficiency criteria
- 4000 Kelvin Cool White color temperature
- Equivalent to a 32-Watt fluorescent T8 tube
- Frosted glass lens evenly diffuses light
- UL listed for use in damp locations
- Bi-Pin G13 base
- DLC® Part Number: PLTSP39214
- NSF/ANSI standard 2 coating

## APPLICATIONS

- Office spaces and work environments
- Kitchens and bathrooms
- Outdoor lighting and garages



SKU#	Kelvin	Lumens	CRI	Wattage	Voltage	DLC?	Base	LED L70 Life Hours	Warranty
PLT-90031	4000	1800	82	15	120-277	YES	Bi-Pin	≥100,000	5 Year

## SPECIFICATIONS

DIMMABLE .....	NO	LUMENS .....	1,800
DLC LISTED .....	YES	VOLTAGE .....	120-277
SAFETY RATING .....	UL DAMP LENS .....	LENTH .....	FROSTED GLASS
CRI .....	82	BASE TYPE .....	G13
COLOR .....	COOL WHITE	BALLAST TYPE .....	BALLAST BYPASS
COLOR TEMPERATURE .....	4000K	DIAMETER .....	1 IN.
LED L70 LIFE HOURS .....	≥100,000	LENGTH .....	48 IN.
WATTAGE .....	15 WATTS	FLUORESCENT EQUAL.....	32 WATT