

LED

4 ft. Plug-and-Play T5 Tube



FEATURES

- Suitable replacement for 54-Watt high output fluorescent T5 tubes
- Operates with an existing electronic ballast
- Works with non-shunted lampholders
- UL listed for damp locations
- Has a miniature bi-pin base
- DLC® Part Number: PLTSP56114

TYPICAL APPLICATIONS

- Office spaces and conference rooms
- Classrooms and hallways
- Hospitals and lobbies



SKU#	Size	Lumens	Wattage	Kelvin	Operation	CRI	DLC?	Base	Warranty
PLT-90020	4 ft.	3500	25W	4000K	Plug-and-Play	83	YES	Miniature Bi-Pin	5 Year

SPECIFICATIONS

BULB SHAPE	T5	FLUORESCENT EQUAL	54-WATT
DIMMABLE	NO	COMPATIBILITY	ELECTRONIC BALLASTS
SAFETY RATING	UL DAMP	LAMPHOLDER(S)	NON-SHUNTED
COLOR	COOL WHITE	LENS	FROSTED GLASS
LED L70 LIFE HOURS	≥100,000	LENGTH	4 IN.
SYSTEM WATTAGE (INCLUDING BALLAST)	28W	DIAMETER	0.6 IN.
VOLTAGE	120-277		