

LED 4 ft. Plug-and-Play T5 Tube

PLT
&
T



FEATURES

- Suitable replacement for 54-Watt high output fluorescent T5 tubes
- Operates with an existing electronic ballast
- Works with non-shunted lampholders
- UL listed for damp locations
- Has a miniature bi-pin base
- DLC® Part Number: PLTSP56115

TYPICAL APPLICATIONS

- Office spaces and conference rooms
- Classrooms and hallways
- Hospitals and lobbies



SKU#	Size	Lumens	Wattage	Kelvin	Operation	CRI	DLC?	Base	Warranty
PLT-90021	4 ft.	3500	25W	5000K	Plug-and-Play	83	YES	Miniature Bi-Pin	5 Year

SPECIFICATIONS

BULB SHAPE	T5		
DIMMABLE	NO	FLUORESCENT EQUAL	54-WATT
SAFETY RATING	UL DAMP	COMPATIBILITY	ELECTRONIC BALLASTS
COLOR	DAYLIGHT WHITE	LAMPHOLDER(S)	NON-SHUNTED
LED L70 LIFE HOURS	≥100,000	LENS	FROSTED GLASS
SYSTEM WATTAGE (INCLUDING BALLAST)	28W	LENGTH	4 IN.
VOLTAGE	120-277	DIAMETER6 IN.