

LED

Ballast Bypass U-Bend T8 LED Tube



FEATURES

- Suitable replacement for 31-Watt T8 U-bend fluorescent tubes
- Operates directly off of 120-277 line voltage
- Works with non-shunted lampholders
- UL listed for damp locations
- Has a Bi-Pin G13 base
- DLC® Part Number: PLTSP89214

TYPICAL APPLICATIONS

- Office spaces and conference rooms
- Classrooms and hallways
- Hospitals and lobbies



SKU#	Leg Spacing	Lumens	Wattage	Kelvin	Operation	CRI	DLC?	Base	Warranty
PLT-90026	1.625 in.	2200	18W	4000K	Ballast Bypass	82	YES	Medium Bi-Pin	5 Year

SPECIFICATIONS

BULB SHAPE	T8	VOLTAGE	120-277
DIMMABLE	NO	FLUORESCENT EQUAL	31-WATT
SAFETY RATING	UL DAMP	LAMPHOLDER(S)	NON-SHUNTED
COLOR	COOL WHITE	LENS	FROSTED GLASS
LED L70 LIFE HOURS	≥100,000	LENGTH	22.425 IN.
LUMENS PER WATT	122	DIAMETER	1.0 IN.
SYSTEM WATTAGE (INCLUDING BALLAST)	21		