

LED

Ballast Bypass U-Bend T8 LED Tube



FEATURES

- Suitable replacement for 31-Watt T8 U-bend fluorescent tubes
- Operates directly off of 120-277 line voltage
- Works with non-shunted lampholders
- UL listed for damp locations
- Has a Bi-Pin G13 base
- DLC® Part Number: PLTSP89215

TYPICAL APPLICATIONS

- Office spaces and conference rooms
- Classrooms and hallways
- Hospitals and lobbies



| SKU# | Leg Spacing | Lumens | Wattage | Kelvin | Operation | CRI | DLC? | Base | Warranty |
|-----------|-------------|--------|---------|--------|----------------|-----|------|---------------|----------|
| PLT-90027 | 1.625 in. | 2200 | 18W | 5000K | Ballast Bypass | 82 | YES | Medium Bi-Pin | 5 Year |

SPECIFICATIONS

| | | | |
|--|----------------|-------------------------|---------------|
| BULB SHAPE | T8 | VOLTAGE | 120-277 |
| DIMMABLE | NO | FLUORESCENT EQUAL | 31-WATT |
| SAFETY RATING | UL DAMP | LAMPHOLDER(S) | NON-SHUNTED |
| COLOR | DAYLIGHT WHITE | LENS | FROSTED GLASS |
| LED L70 LIFE HOURS | ≥100,000 | LENGTH | 22.425 IN. |
| LUMENS PER WATT | 122 | DIAMETER | 1.0 IN. |
| SYSTEM WATTAGE (INCLUDING BALLAST) | 21 | | |