



S29769

75W/LED/HID/MB/5000K/100-277V/EX39
 75 watt - LED HID Replacement; 5000K; Mogul Extended base;
 Adjustable beam angle; 100-277 volts

Features

- Replaces HID, CFL, and Incandescent
- Direct wire range voltage 100-277V
- Approved for totally enclosed fixtures
- Hi bay, low bay and post top
- Light panels lock into place creating 3 separate beam angle options
- IP65 rated
- 5 year limited warranty

Specification note: Power Factor >0.9; Operating temperature range -20°C to 65°C; Operating Frequency 50-60Hz; Working Voltage AC 90-305V

Optional accessory: In-line surge protector 80-929

Width (360°)	Width (270°)	Width (180°)
4.2"	9.3"	10.9"

Minimum Compartment Size		
Length	Width	Depth
9.25 inch	9.25 inch	8.27 inch



S29769



Item Number	Product Line	UPC	Input Voltage	Watts	Incandescent Equivalent	Fluorescent Equivalent	HID Equivalent
S29769	Hi-Pro	045923297694	100 - 277	75	750W	105W	400W

Base	ANSI Base	Lamp Code	Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches	Initial Lumens
Mogul Extended	EX39	75W/LED/HID/MB/5000K/100-277V/EX39	Non-Dimmable	White	8-5/8"	4-3/16" (Open 10-7/8")	9800

Average Rated Hours	Kelvin Temp	Color	CRI	Beam Spread Deg	Pack	DLC® Part Number	RoHS Compliant
50000	5000	Stark White	80+	Adjustable: 360; 270; 180	6	S29769	Yes

Fixture Type	UL Classification	Warranty	Thermal Management
Enclosed Rated	cULus - Wet Location Rated	5 Year Limited	More Details About*

*Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature Control). If the lamp heats up in an application to 110°C, it will automatically reduce itself to 70% of rated wattage. If the ambient temperature continues to increase and reaches 120°C, it will reduce itself to 50% of rated wattage. In the event this happens, the lamps will remain at that level until they are turned off at which time they will reset and come back on a full brightness.