
HID LED 25W 277V EX39 TITANIUM LED SERIES











- Direct line voltage 120-277V Not compatible with ballasts
- Omnidirectional: 290° beam angle
- Exceptional efficacy 132 LPW in Hologen White
- Frosted diffuser maintains low glare
- Compatible with EX39 & E39 sockets
- Suitable for use in totally enclosed fixtures
- DLC® Part Number: 25HID/850/277V/EX39





















UNIVERSAL



EFFICACY

HID LED PRODUCT FEATURES

Suitable for Enclosed Fixtures



This HID LED lamp replaces a 50-100W HID and is suitable for use in enclosed fixtures. Its high lumen output and exceptional efficacy make it an ideal choice for bollard, post top, low bay and other outdoor applications.

Omnidirectional Lighting


LED lamps.






HID LED 25W 277V EX39 TITANIUM LED SERIES









SPECIFICATIONS

Product	97968	97969	97970	
Model	25HID/830/277V/EX39	25HID/840/277V/EX39	25HID/850/277V/EX39	
Туре	A23	A23	A23	
Base	EX39	EX39	EX39	
Power (W)	25	25	25	
Voltage - Frequency	120-277V 50/60Hz	120-277V 50/60Hz	120-277V 50/60Hz	
Color Temp. (ANSI)	Warm White 3000K	Cool White 4000K	Daylight 5000K	
CRI (Ra) (typ.)	82	82	82	
Typical lumens (lm)	3200	3300	3400	
Efficacy (LPW)	128	132	136	
Beam Angle	290°	290°	290°	
Dimmable	No	No	No	
Power Factor	0.9	0.9		
Rated Lifetime - L70 (hrs.)	50,000	50,000 50,000		
Temperature Rating	-4°F/-20°C - 95°F/35°C	-4°F/-20°C - 95°F/35°C -4°F/-20°C - 95°F/35°C		
Dia. x MOL	3.23"x6.81" (82x173mm)	3.23"x6.81" (82x173mm) 3.23"x6.81" (82x173mm)		
Weight (lb. / g)	1.10lb. / 500g	1.10lb. / 500g 1.10lb. / 500g		

HID EQUIVALENCE

GREEN CREATIVE HID LED		Metal Halide		Mercury Vapor		High Pressure Sodium	
Power	Lumens	Power	Mean Lumens	Power	Mean Lumens	Power	Mean Lumens
25W	3300	70W	3400	100W	3300	50W	3600

^{*} Savings per lamp based on \$0.11 / kw energy cost, 12 hrs / day lamp usage, \$12 HID with 10,000-hr lifetime, \$70 ballast, \$60 LED HID with 50,000-hr lifetime
** Suitable for use in totally enclosed fixtures
*** Suitable for damp locations. Not for use where directly exposed to weather or water