



S29751

40W/LED/HID/MB/5000K/100-277V/EX39
 40 watt - LED HID Replacement; 5000K; Mogul extended base;
 Adjustable beam angle; 100-277 volts

Features

- Replaces HID, CFL, and Incandescent
- Direct wire range voltage 100-277V
- Approved for totally enclosed fixtures
- Hi bay, low bay and post top
- Light panels lock into place creating 3 separate beam angle options
- IP65 rated
- Built-in surge protection - 1KV
- 5 year limited warranty

Specification note: Power Factor >0.9; Operating temperature range -20°C to 65°C; Operating Frequency 50-60Hz; Working Voltage AC 90-305V

Optional accessory: In-line surge protector 80-929

Width (360°)	Width (270°)	Width (180°)
3.5"	7.7"	8.9"

Minimum Compartment Size		
Length	Width	Depth
8.27 inch	9.25 inch	9.25 inch



S29751



Item Number	Product Line	UPC	Input Voltage	Watts	Incandescent Equivalent	Fluorescent Equivalent	HID Equivalent
S29751	Hi-Pro	045923297519	100 - 277	40	300W	65W	175W

Power Factor	Base	ANSI Base	Lamp Code			Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches
0.90	Mogul Extended	EX39	40W/LED/HID/MB/5000K/100-277V/EX39			Non-Dimmable	White	7-7/8"	3-1/2" (Open 8-7/8")
Initial Lumens	Average Rated Hours	Kelvin Temp	Color	CRI	Beam Spread Deg	Operating Temperature			Pack
5200	50000	5000	Stark White	80+	Adjustable: 360; 270; 180	-20C (-4F) to a maximum of +65C (+149F)			12/6
DLC® Part Number:		RoHS Compliant		Fixture Type		UL Classification		Warranty	
S29751		Yes		Enclosed Rated		cULus - Wet Location Rated		5 Year Limited	