





FEATURES

- For Commercial and Industrial Buildings
- 400 Watt Metal Halide Equivalent
- Compatible with 0-10V Dimmer
- UL Listed for Damp Locations
- UL File No: E484679
- 120° Beam Angle
- IP65 Rating



ENERGY EFFICIENCY & LONG LIFE


75% MORE ENERGY EFFICIENT THAN STANDARD MH LAMPS TYPICAL PAYBACK OF 1 - 3 YEARS


SKU#	Kelvin	Lumens	Shape	Wattage	Voltage	DLC?	Mounting	Life Hours	Warranty
PLT-11082-4K	4000	20,100	Round	150	120-277	No	Ring	60,000	3 Years

ADDITIONAL PHOTOS













VEC

FEATURES

- Polycarbonate Lens
- Lightweight design
- LED Driver Included

TYPICAL APPLICATIONS

- Industrial Factories
- Distribution Centers
- Cold Storage Facilities

WARRANTY

Warranty

3 Years

SPECIFICATIONS

DIMANAADIE

DIIVIIVIABLE	1E3
DLC LISTED	No
SAFETY RATING	UL
CRI	80
COLOR	COOL WHITE
COLOR TEMPERATURE	4000K
LIFE HOURS	60,000
WATTAGE	150 WATTS
LUMENS	20,100
VOLTAGE	120-277
FINISH	BLACK
HOUSING	ALUMINUM
MOUNTING	RING MOUNT
LENS	POLYCARBONATE
DIAMETER	12.91 IN.
HEIGHT	7.87 IN
WEICHT	67100

PHOTOMETRICS

