

Item#: PLT-20207 LED 1x4 LOUVERED HIGH BAY

HIGH-BAY LUMINAIRES FOR COMMERCIAL AND INDUSTRIAL BUILDINGS

FEATURES

- · Provides smooth uniform light.
- Low-profile which meets limitless range of applications.
- Use 30% less energy than a linear fluorescent fixtures
- Die formed 24 gauge cold rolled steel.
- All steel surfaces are painted after fabrication with high gloss baked white matte powder paint.

APPLICATION

Ideal for larger warehouses, retail applications, commercial buildings and work areas.

ELECTRICAL

Wattage	90W
Voltage	120-277V
Power Factor	0.9
Total Harmonic Distortion (THD)	10
LIGHTING DEDECOMANCE	

LIGHTING PERFORMANCE

Lumens	11700	
Lumens Per Watt (Lm/W)	130	
Color Temperature (CCT)	4000K	
Color Rendering (CRI)	80	
R9 (Red Value)		
R13 (Skin Tones)		
Beam Angle	120°	
Light Distribution	Type VS	
Dimmable Lighting Control	(Dimmable 0-10V, Range 10% - 100%	

ENVIRONMENT

Operating Temperature	-4° ~ 122°F		
Suitable Location	DAMP		
Ingress Protection Rating	IP40		

LIFESPAN

Average Life (Hours)	50,000
Warranty (Years)	5

COMPONENTS

LED Light Source	Seoul STWxA2PD-xx	
Driver	Simon SI 80-I2000 120-277 W D1 S	

CONSTRUCTION

Housing	24 Gauge Steel		
Base / Power Supply	Hard Wired		
Finish	White		

QUALIFICATIONS




Published lumens on LED products are approximate and may vary slightly.

Item#: PLT-20207 LED 1x4 LOUVERED HIGH BAY

DIMENSIONS (Inches)

, ,	
Length	48.1"
Width/Diameter	9.8"
Height	4.2"
Weight (Lbs)	
Height	4.2"

Line drawings may not be to scale and are for general reference only.



PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	1	811768027440		
Country of Origin	China			
HS Tariff				

ORDERING

ITEM#	DESCRIPTION	CASE	
PLT-20207	LED 1x4 LOUVERED HIGH BAY - 90W/40K/120-277V/DIMMABLE - SUPERIOR LIFE® DLC ®	1	
ACCESSORIES/REPLACEMENT PARTS			
PLT-54896	360° LED LOW/HIGH BAY FIXTURE PIR OCCUPANCY SENSOR 800W/1200W-120-277V - SUPERIOR LIFE®	50	