

55244

LED 96" DESIGNER STRIP

TECHNICAL DATA SHEET

FEATURES



DIRECT LINEAR AMBIENT LUMINAIRES

- Provides smooth uniform light.
- Low-profile which meets limitless range of applications.
- Use 30% less energy than a linear fluorescent fixtures

HOUSING

- Die formed 24 gauge cold rolled steel.
- All steel surfaces are painted after fabrication with high gloss baked white matte powder paint.
- Diffusing lens for soft even light

MOUNTING

Designed for surface, pendant or stem mounted.

DIMMING

- 0-10V dimming function, dimming range is 10% - 100%

APPLICATION


Larger warehouses, retail applications, commercial buildings and work areas.

SPECIFICATIONS

Power Consumption	65W
Input Voltage	120-277V
Power Factor	0.9
THD	10
Lumens	8645
Luminous Efficiency	133 Lm/W
Color Temperature	5000K
CRI	80
Housing	24 Gauge Steel
Finish	White
Dimensions (Inches)	96"(L) x 3.4"(W) x 3.6"(D)
LIFESPAN & ENVIRONMENT	
Average Life	50,000
Operating Temperature	-20°C ~ 50°C



DIMENSIONS



DIMMER COMPATABILITY

Only the following dimmers have been tested, by no means is this list complete:

LUTRON

DIVADVSTV
MAESTRO MS-Z101
NOVA T NTSTV

LEVITON

ILLUMATECH IP710-LFZ

PHILIPS

SUNRISE SR1200ZTUNV

ORDERING

ITEM#	DESCRIPTION	WATTS	COLOR	LUMENS	CRI	VOLTS	HOURS	CASE
55244	LED 96" DESIGNER STRIP - 65W/50K/120-277V/DIMMABLE	65	5000K	8645	80	120-277	50,000	6