

FLF15 / FLF30 / FLF50



Flood lights

This series has a thin, smart and stylish shape with excellent cooling and high lumen efficacy of 115-120 lm/w. With various mounting options, this series is a great choice for anyone needing large amounts of light at a energy saving cost.

Features

- Corrosion-Resistant Coating Finish
- Imported high-dense aluminum alloy housing
- High transparency and weather resistant lens
- Color options: **Bronze**, Black, White, Gray

Applications

- Architecture
- Sports grounds
- Billboards
- High Ways
- Tunnels, Bridges



Installation Diagram

Specifications

General	Model:	FLF15	FLF30	FLF50
	Lumen Efficacy:	115 lm / w	115 lm / w	120 lm / w
	Lumen Output:	1,725 lm	2,700 lm	6,000 lm
Electrical	Input Power:	15W	30W	50W
	Input Voltage:	100-277V	100-277V	100-277V
	Power Factor:	>90%	>90%	>90%
Color	Color Temperature (CCT):	3000k - 5700k	3000k - 5700k	3000k - 5700k
	Color Rendering Index (CRI):	>80	>80	>80
Operational	Dimmable:	No	No	No
	Dimensions:	Yoke Knuckle 4.66 in x 4.25 in x 1.5 in 6.89 in x 4.76 in x 3.07 in	6.6 in x 6.75 in x 1.6 in 4.72 in x 3.27 in x 2.60 in	7.8 in x 8.5 in x 1.8 in 8.62 in x 5.94 in x 3.54 in
	Rating:	IP65	IP65	IP65
	Warranty:	5 Year	3 Year	5 Year
	Mounting Option:	YK(Yoke)/KN (Knuckle)	YK(Yoke)/KN (Knuckle)	YK(Yoke)/KN (Knuckle)