



FEATURES

- Bypasses ballast to connect to 120-277 line voltage, eliminating compatibility issues
- Includes 6kV surge protection to prevent against electricity spikes
- IP64 rated, dust-tight and water resistant
- Provides an efficient replacement for 175W HID fixtures
- Emits light at an all-encompassing 360 degree beam angle

SKU#	Kelvin	Lumens	Base	Wattage	Voltage	DLC?	Mounting	Life Hours	Warranty
PLT-11609	5000	6,525	Medium	45	120-277	No	Universal	50,000	1 Year

ADDITIONAL PHOTOS



9.72"

FEATURES

- Direct line voltage 120-277V - Ballast Bypass
- Replaces 175W HID fixtures
- 6kV surge protection

SPECIFICATIONS

DIMMABLE	NO
DLC LISTED	NO
SAFETY RATING	UL
CRI	80
COLOR	DAYLIGHT WHITE
COLOR TEMPERATURE	5000K
LIFE HOURS	50,000
WATTAGE	45 WATTS
LUMENS	6,525
VOLTAGE	120-277
FINISH.....	WHITE
HOUSING	ALUMINUM
MOUNTING	UNIVERSAL
LENGTH	3.78 IN.
HEIGHT	9.72 IN.
WIDTH	3.78 IN.
WEIGHT	1.9 LBS.

TYPICAL APPLICATIONS

- Schools, Factories, Hotels
- Offices, Conference Rooms
- Hospitals

WARRANTY

Warranty

1 Year

WIRE DIAGRAM

Replacing HPS/HID Lamp

