

LED T8 SERIES


Dimmable Direct-Wire

COMMERCIAL SPEC GRADE

Replaces 32W 4ft Fluorescent T8



Superior All-Around Light Distribution



Coated Shatter-Resistant Glass



Proprietary IC-Driver design allows for high efficiency and exceptional longterm performance



ARCHIPELAGO® Light Engine produces uniform light output from end-to-end



FEATURES

- Dimmable Direct-Wire: 120V Input, TRIAC Dimming Protocol
- Operates with Wide Range of Traditional Dimmers
- Full Glass Lens with 310° Light Distribution
- Uniform Light Output From End-to-End
- UL + NSF + DLC4 QPL Listed
- Instant-ON with No Flicker
- 5-Year Warranty

Specifications and Technical Data (T8 | Dimmable Direct-Wire)


MODEL	BASE TYPE	WATTS / EQV.	LUMEN	CCT	LENGTH	VOLTAGE	CRI	THD	CARTON QTY	LIGHT DISTRIBUTION
LBN8F1841	G13	18W / 32W	2200LM	4100K	4 FT	120V	83	<20%	16	310°
LBN8F1841	G13	18W / 32W	2250LM	5000K	4 FT	120V	83	<20%	16	310°

* Suitable for use in totally enclosed fixtures.

** Suitable for damp locations.

*** Visit <http://www.archipelagolighting.com/support> for installation instructions.

Installation Configuration



Light Distribution Curve

