



LED Recessed Retrofits

DIMMABLE • 35,000 HOURS • EASY INSTALLATION

TCP's Dimmable Retrofit Kits are the perfect choice for new construction and retrofit opportunities when a sleek, integrated look is preferred.

LIMITLESS OPTIONS FOR THE FOLLOWING APPLICATIONS

- Commercial
- Industrial
- Retail
- Residential
- Healthcare

FEATURES

Long life: 35,000 hours

Very low heat generation

Excellent color consistency and CRI

Mounts directly to recessed can:
4 or 5/6 inch

Shatter resistant

Smooth, uniform dimming from 100 - 5%

BENEFITS

Minimizes replacement and maintenance costs

Perfect for sensitive display lighting such as art galleries

Enhances colors of focal point while maintaining uniformity throughout lighting installation from lamp to lamp

Easy installation and integrated trim
Pigtail and spring clips

Lower the risk of injury and breakage

SPECIFICATIONS

Color Temperatures..... 2700K, 3000K, 3500K, 4100K, 5000K
Wattage options 14W, 11W, 10W, 9W
Input Line Voltage 120 VAC
Input Line Frequency..... 50/60HZ
Lamp Life (Rated) 35,000 hours
Minimum Starting Temp -22F/-30C
Maximum Operating Temp..... 40°C
CRI..... 80, 90

IC-rated for direct contact with insulation

UL approved for damp location (indoor only)—outdoor environment may cause yellowing of the white trim.
This is not covered by warranty.



5 YEAR WARRANTY
*Based on 12 hours use per day



RoHS COMPLIANT



LED
we know light.™





LED RECESSED RETROFITS

DIMMABLE • 35,000 HOURS • EASY INSTALLATION

ITEM #	DESCRIPTION	ENERGY STAR V2.1	VOLTAGE	LED WATTS	REPLACEMENT	LUMENS	LPW	CRI	COLOR TEMP	MOL (inches)	DIA (inches)	CASE QUANTITY
--------	-------------	------------------------	---------	--------------	-------------	--------	-----	-----	---------------	-----------------	-----------------	------------------

5/6" Recessed Retrofits

120 Watt Replacement • 35,000 Hour

LED14DR5627K	LED 5/6" 12W DIM 120W EQ - 2700K	★	120V	12	120	1250	89.3	80	2700K	3.0	7.4	6
LED14DR5630K	LED 5/6" 12W DIM 120W EQ - 3000K	★	120V	12	120	1300	92.9	80	3000K	3.0	7.4	6
LED14DR5641K	LED 5/6" 12W DIM 120W EQ - 4100K	★	120V	12	120	1300	92.9	80	4100K	3.0	7.4	6
LED14DR5650K	LED 5/6" 12W DIM 120W EQ - 5000K	★	120V	12	120	1350	96.4	80	5000K	3.0	7.4	6

75 Watt Replacement • 35,000 Hour

LED11DR5627K	LED 5/6" 9.5W DIM 75W EQ - 2700K	★	120V	9.5	75	850	72.7	80	2700K	3.0	7.4	6
LED11DR5630K	LED 5/6" 9.5W DIM 75W EQ - 3000K	★	120V	9.5	75	850	77.3	80	3000K	3.0	7.4	6
LED11DR5641K	LED 5/6" 9.5W DIM 75W EQ - 4100K	★	120V	9.5	75	875	81.8	80	4100K	3.0	7.4	6
LED11DR5650K	LED 5/6" 9.5W DIM 75W EQ - 5000K	★	120V	9.5	75	900	86.4	80	5000K	3.0	7.4	6

HiCRI • 65 Watt Replacement • 35,000 Hour

L11DR56D3527K95**	LED 5/6" 11W HiCRI DIM 65W EQ - 2700K	★	120V	11	65	700	63.6	90	2700K	3.125	7.4	6
L11DR56D3530K95**	LED 5/6" 11W HiCRI DIM 65W EQ - 3000K	★	120V	11	65	750	86.2	90	3000K	3.125	7.4	6

4" Recessed Retrofits

75 Watt Replacement • 35,000 Hour

LED10DR427K	LED 4" 10W DIM 75W EQ - 2700K	★	120V	10	75	750	75.0	80	2700K	3.0	5.0	6
LED10DR430K	LED 4" 10W DIM 75W EQ - 3000K	★	120V	10	75	750	75.0	80	3000K	3.0	5.0	6
LED10DR435K	LED 4" 10W DIM 75W EQ - 3500K		120V	10	75	620	62.0	80	3500K	3.0	5.0	6
LED10DR441K	LED 4" 10W DIM 75W EQ - 4100K	★	120V	10	75	800	80.0	80	4100K	3.0	5.0	6
LED10DR450K	LED 4" 10W DIM 75W EQ - 5000K	★	120V	10	75	800	80.0	80	5000K	3.0	5.0	6

HiCRI • 50 Watt Replacement • 35,000 Hour

L9DR4D3527K95**	LED 4" 9W HiCRI DIM 50W EQ - 2700K		120V	9	50	550	61.1	90	2700K	3.0	5.2	6
L9DR4D3530K95**	LED 4" 9W HiCRI DIM 50W EQ - 3000K		120V	9	50	550	61.1	90	3000K	3.0	5.2	6

* JA8 Compliant

+ All Plastic Body

