



# S16402

12T8/LED/HO-SIGN/36-840/BP  
 12W T8 LED; 4000K; 1500 Lumens; 120-277V; Type B; Single Ended; Ballast Bypass

## Features

- Meets NSF/ANSI Standard 2 requirements for certified use in food handling areas.
- No ballast or external driver required
- Base rotates 90° for easy installation
- Direct wire 120-277V line voltage\*



S16402

Item Number	UPC	Voltage	Watts	Operating Frequency	Lamp Shape	Base	ANSI Base
S16402	045923164026	120-277	12	50/60Hz	T8	Recessed Double Contact HO/VHO	R17d

  

Lamp Code	Finish	MOL In Inches	MOD In Inches	Initial Lumens	Average Rated Hours	Kelvin Temp	Color
12T8/LED/HO-SIGN/36-840/BP	Frosted	36"	1.00"	1500	50000	4000	Cool White

  

CRI	Beam Spread Deg	Operating Temperature	Pack	Package Type	CEC Status	RoHS Compliant	UL or ETL Listed
83	330	-40C (-40F) to a maximum of +45C (+113F)	10	Sleeve	Not Approved	Yes	UL

  

UL Classification	Warranty
cULus Classified - Damp Location Rated	5 Year Limited