



# S16410

36T8/LED/HO-SIGN/96-840/BP  
36W T8 LED; 4000K; 5000 Lumens; 120-277V; Type B; Single Ended; Ballast Bypass

## Features

- Meets NSF/ANSI Standard 2 requirements for certified use in food handling areas.
- No ballast or external driver required
- Base rotates 90° for easy installation
- Direct wire 120-277V line voltage\*



S16410

| Item Number | UPC          | Voltage | Watts | Operating Frequency | Lamp Shape | Base                           | ANSI Base |
|-------------|--------------|---------|-------|---------------------|------------|--------------------------------|-----------|
| S16410      | 045923164101 | 120-277 | 36    | 50/60Hz             | T8         | Recessed Double Contact HO/VHO | R17d      |

| Lamp Code                  | Finish  | MOL In Inches | MOD In Inches | Initial Lumens | Average Rated Hours | Kelvin Temp | Color      |
|----------------------------|---------|---------------|---------------|----------------|---------------------|-------------|------------|
| 36T8/LED/HO-SIGN/96-840/BP | Frosted | 96"           | 1.00"         | 5000           | 50000               | 4000        | Cool White |

| CRI | Beam Spread Deg | Operating Temperature                    | Pack | Package Type | CEC Status   | RoHS Compliant | UL or ETL Listed |
|-----|-----------------|--|------|--------------|--------------|----------------|------------------|
| 83  | 330             | -40C (-40F) to a maximum of +45C (+113F) | 10   | Sleeve       | Not Approved | Yes            | UL               |

| UL Classification                      |  |  |  | Warranty       |  |  |  |
|--|--|--|--|----------------|--|--|--|
| cULus Classified - Damp Location Rated |  |  |  | 5 Year Limited |  |  |  |