



LED Classic Filament Decorative Lamps

DIMMABLE • OMNIDIRECTIONAL • 15,000 HOURS

TCP's filament style LED decorative lamps create a relaxing atmosphere with decorative touches that light up the rooms. Exclusive LED technology provides unmatched longevity and perfect 5-100% dimming.

LIMITLESS OPTIONS FOR THE FOLLOWING APPLICATIONS

- Accent Lighting
- Wall Sconces
- Decorative Lighting
- Chandeliers
- Ceiling Fans

FEATURES	BENEFITS
Energy efficient	Up to 85% less energy than halogen lamps
Very low heat generation	Minimizes replacement and maintenance costs
Long life	15,000 hours rated life
UL approved for damp and enclosed locations	Can be used outdoors when protected from elements. Withstands humidity indoors/outdoors
Appearance	Unique filament LED configuration provides a uniform color output
ANSI construction compliant	Fits most general applications

★ Smooth, Uniform Dimming from 5 - 100% ★

SPECIFICATIONS

Color Temperatures.....	2200K, 2700K, 3000K, 4000K, 5000K
Input Line Voltage	120 VAC
Input Line Frequency.....	50/60HZ
Lamp Life (Rated)	15,000 hours
Minimum Starting Temp	-30°C
Maximum Operating Temp.....	40°C
CRI	>80
Base	E12/E26



3 YEAR WARRANTY
*Based on 12 hours use per day

RoHS COMPLIANT



25W/40W/60W
FB11
E12 base



25W/40W/60W
FB11
E26 base



25W/40W/60W
FF11
E12 base



25W/40W/60W
FF11
E26 base





LED CLASSIC FILAMENT DECORATIVE LAMPS

DIMMABLE • OMNIDIRECTIONAL • 15,000 HOURS

ITEM #	DESCRIPTION	ENERGY STAR V2.1	LED WATTS	INCAND. WATTS	LUMENS	CRI	COLOR TEMP	GLASS TYPE	MOL (inches)	DIA (inches)	BASE
--------	-------------	------------------	-----------	---------------	--------	-----	------------	------------	--------------	--------------	------

B11 *continued*

60 Watt Replacements • Dimmable • E12 Base • 15,000 Hour

FB11D6022EE12CS	B11 60W 2200K CLEAR E12		5.0	60	500	>80	2200K	Clear	4.1	1.4	E12
FB11D6027EE12CS	B11 60W 2700K CLEAR E12	★	5.5	60	500	>80	2700K	Clear	4.1	1.4	E12
FB11D6027EE12W	B11 60W 2700K FROST E12		5.0	60	500	>80	2700K	Frosted	4.1	1.4	E12
FB11D6030EE12CS	B11 60W 3000K CLEAR E12	★	5.0	60	500	>80	3000K	Clear	4.1	1.4	E12
FB11D6040EE12CS	B11 60W 4000K CLEAR E12	★	5.0	60	500	>80	4000K	Clear	4.1	1.4	E12
FB11D6050EE12CS	B11 60W 5000K CLEAR E12		5.0	60	500	>80	5000K	Clear	4.1	1.4	E12
FB11D6050EE12W	B11 60W 5000K FROST E12		5.0	60	500	>80	5000K	Frosted	4.1	1.4	E12

60 Watt Replacements • Dimmable • E26 Base • 15,000 Hour

FB11D6022KC	B11 60W 2200K CLEAR		5.0	60	475	>80	2200K	Clear	3.8	1.4	E26
FB11D6022KW	B11 60W 2200K FROSTED		5.0	60	475	>80	2200K	Frosted	3.8	1.4	E26
FB11D6027EC	B11 60W 2700K CLEAR	★	5.0	60	500	>80	2700K	Clear	3.8	1.4	E26
FB11D6027EW	B11 60W 2700K FROSTED		5.0	60	500	>80	2700K	Frosted	3.8	1.4	E26
FB11D6050EC	B11 60W 5000K CLEAR	★	5.0	60	500	>80	5000K	Clear	3.8	1.4	E26
FB11D6050EW	B11 60W 5000K FROSTED		5.0	60	500	>80	5000K	Frosted	3.8	1.4	E26

F11

25 Watt Replacements • Dimmable • E12 Base • 15,000 Hour

FF11D2522KE12C	F11 25W 2200K CLEAR E12		3.0	25	225	>80	2200K	Clear	3.8	1.4	E12
FF11D2522KE12W	F11 25W 2200K FROSTED E12		3.0	25	225	>80	2200K	Frosted	3.8	1.4	E12
FF11D2527EE12C	F11 25W 2700K CLEAR E12	★	3.0	25	250	>80	2700K	Clear	3.8	1.4	E12
FF11D2527EE12W	F11 25W 2700K FROSTED E12		3.0	25	250	>80	2700K	Frosted	3.8	1.4	E12
FF11D2530EE12C	F11 25W 3000K CLEAR E12		3.0	25	250	>80	3000K	Clear	3.8	1.4	E12
FF11D2540EE12C	F11 25W 4000K CLEAR E12	★	3.0	25	250	>80	4000K	Clear	3.8	1.4	E12
FF11D2550EE12C	F11 25W 5000K CLEAR E12		3.0	25	250	>80	5000K	Clear	3.8	1.4	E12
FF11D2550EE12W	F11 25W 5000K FROSTED E12		3.0	25	250	>80	5000K	Frosted	3.8	1.4	E12

25 Watt Replacements • Dimmable • E26 Base • 15,000 Hour

FF11D2522KC	F11 25W 2200K CLEAR		3.0	25	225	>80	2200K	Clear	3.6	1.4	E26
FF11D2522KW	F11 25W 2200K FROSTED		3.0	25	225	>80	2200K	Frosted	3.6	1.4	E26
FF11D2527EC	F11 25W 2700K CLEAR		3.0	25	250	>80	2700K	Clear	3.6	1.4	E26
FF11D2527EW	F11 25W 2700K FROSTED		3.0	25	250	>80	2700K	Frosted	3.6	1.4	E26
FF11D2550EC	F11 25W 5000K CLEAR		3.0	25	250	>80	5000K	Clear	3.6	1.4	E26
FF11D2550EW	F11 25W 5000K FROSTED		3.0	25	250	>80	5000K	Frosted	3.6	1.4	E26

continued



RoHS
COMPLIANT

3 YEAR
WARRANTY

*Based on 12 hours use per day