

LED VALUE A-LAMP
A19 NON-DIM VALUE SERIES



6W & 9W



11W & 14W



PRODUCT DESCRIPTION:

MaxLite's LED VALUE A-Line lamps replicate true A19 incandescent that produces even light in all directions. They are suited to a wide variety of residential and commercial applications, pendants, wall sconces and table and floor lamps..

FEATURES:

- 6 Watts (40W Equivalent, 450 Lumens)
- 9 Watts (60W Equivalent, 800 Lumens)
- 11 Watts (75W Equivalent, 1100 Lumens)
- 14 Watts (100W Equivalent, 1500 Lumens)
- 11,000 hour life (L70 standards)
- CCT: 2700K, 3000K, 4000K & 5000K
- CRI: ≥ 80
- Non-Dimmable
- Enclosed rated
- Saves more than 84 percent on energy
- Power factor: ≥0.6
- Standard E26 base
- Mercury-free
- RoHS Compliant
- One year limited warranty

APPLICATIONS

- Table and floor lamps
- Sconces
- Approved for use in fully enclosed luminaires
- Suitable for use in damp locations

ORDERING:

MODEL SELECTION (Full list of order codes on pg. 2)		Typical order example:		
LAMP	BASE	DIMMABILITY	FAMILY	CCT
E6A19= Enclosed, 6 Watts, A19 E9A19= Enclosed, 9 Watts, A19 E11A19= Enclosed, 11 Watts, A19 E14A19= Enclosed, 14 Watts, A19	(OMIT)= E26	ND= Non-Dimmable	V= Value	27= 2700K 30= 3000K 40= 4000K 50= 5000K

SPECIFICATIONS:

E6A19NDVxx

E9A19NDVxx

E11A19NDVxx

E14A19NDVxx

ITEM	SPECIFICATION	DETAILS			
GENERAL PERFORMANCE	Power Consumption	6W	9W	11W	14W
	Lumens Delivered	450	800	1,100	1,500
	Efficacy (lm/w)	75	89	100	107
	CRI	≥80			
	Color Temperature (CCT)	2700K, 3000K, 4000K & 5000K			
	Lumen Maintenance (L70)	11,000 Hours			
	Dimmable	No			
ELECTRICAL	Power Factor	≥0.80			
	Input Voltage	120V			
PHYSICAL	Base Type	E26			
	Operating Temperature	-4°F - 104°F			
CERTIFICATION	Environment	Dry, Damp			
	Warranty	1 Year Limited			

Lighting layouts and spacing criteria available upon request

ORDERING:

ORDER CODE	MODEL NUMBER	INPUT WATTAGE	EQUIVALENT WATTAGE	DELIVERED LUMENS	EFFICACY (LM/W)	CRI	CCT (K)	DIMENSIONS (D" x MOL")
102600	E6A19NDV27	6	40W Inc.	450	75	80	2700K	2.36" x 4.16"
102602	E6A19NDV30	6	40W Inc.	450	75	80	3000K	2.36" x 4.16"
102603	E6A19NDV50	6	40W Inc.	450	75	80	5000K	2.36" x 4.16"
102604	E9A19NDV27	9	60W Inc.	800	89	80	2700K	2.36" x 4.16"
102608	E9A19NDV27/4P	9	60W Inc.	800	89	80	2700K	2.36" x 4.76"
102953	E9A19NDV27/4P/WS	9	60W Inc.	800	89	80	2700K	2.36" x 4.76"
102606	E9A19NDV30	9	60W Inc.	800	89	80	3000K	2.36" x 4.16"
103100	E9A19NDV40	9	60W Inc.	800	89	80	4000K	2.36" x 4.16"
103102	E9A19NDV40/4P	9	60W Inc.	800	89	80	4000K	2.36" x 4.76"
102607	E9A19NDV50	9	60W Inc.	800	89	80	5000K	2.36" x 4.16"
102610	E9A19NDV50/4P	9	60W Inc.	800	89	80	5000K	2.36" x 4.76"
102951	E9A19NDV50/4P/WS	9	60W Inc.	800	89	80	5000K	2.36" x 4.76"
102575	E11A19NDV27	11	75W Inc.	1100	100	80	2700K	2.36" x 4.29"
102576	E11A19NDV30	11	75W Inc	1100	100	80	3000K	2.36" x 4.29"
102577	E11A19NDV50	11	75W Inc	1100	100	80	5000K	2.36" x 4.29"
102578	E14A19NDV27	14	100W Inc	1500	107	80	2700K	2.36" x 4.79"
102589	E14A19NDV27/4P	14	100W Inc	1500	107	80	2700K	2.36" x 4.76"
102956	E14A19NDV27/4P/WS	14	100W Inc	1500	107	80	2700K	2.36" x 4.76"
102579	E14A19NDV30	14	100W Inc	1500	107	80	3000K	2.36" x 4.79"
103103	E14A19NDV40	14	100W Inc	1500	107	80	4000K	2.36" x 4.79"
103104	E14A19NDV40/4P	14	100W Inc	1500	107	80	4000K	2.36" x 4.76"
102580	E14A19NDV50	14	100W Inc	1500	107	80	5000K	2.36" x 4.79"
102591	E14A19NDV50/4P	14	100W Inc	1500	107	80	5000K	2.36" x 4.76"
102957	E14A19NDV50/4P/WS	14	100W Inc	1500	107	80	5000K	2.36" x 4.76"

NOTES:

1. 9W and 14W lamps are available in 4 packs