Recommended Dimmers for Cree® 4" Recessed Downlight 75W LED Bulbs.

Cree LED bulbs are designed to be dimmed with standard incandescent type dimmers and are compatible with most Electric Low Voltage (ELV) dimmers. This list was generated from lab testing of samples and your results may vary.*



Bulbs Per Dimmer Part Phase Rating Works Best With Manufacturer Series Number Load Type Cut Edge (W) min max Ace 3247939 Incandescent Leading 600 12 No flickering or Legrand WideSlide 90680 Incandescent Leading 600 1 12 shimmer observed DSL-06 600/150 12 and smooth dimming Leviton Decora LED/CFL/INC Leading 1 across range. Leviton Illumatech IPL06 Incandescent Leading 600 1 12 No audible noise. Leviton Sureslide 6615 ELV Trailing 300 1 18 CFL/LED Leviton Sureslide 6673 Leading 600/150 1 12 Sureslide 6674 LED/CFL/Inc Leading 600/150 1 12 Leviton 12 Leviton Trimatron 6602 Incandescent Leading 600 1 6683 600 12 Leviton Trimatron Incandescent Leading 1 PD-6WCL CFL/LED 12 Lutron Caseta Wireless Leading 600/150 1 Credenza **TTCL-100** LED 250 5 Lutron Leading Lutron Diva DV-10P Incandescent Leading 1000 1 18 Lutron Diva DV-600P Incandescent Leading 600 1 12 CFL/LED 600/150 Lutron Diva DVCL-153P Leading 1 12 Diva DVELV-303P ELV Trailing 300 18 Lutron FAELV-500 27 Lutron Faedra ELV Trailing 500 1 CFL/LED 12 Lumea LGCL-153 600/150 Lutron Leading Maestro **MACL-153** CFL/LED Leading 600/150 1 12 Lutron RadioRA 2 RRD-6ND 600 12 Incandescent Leading Lutron Skylark S-10P Incandescent 1000 1 18 Lutron Leading Skylark SELV-300P ELV Trailing 300 18 Lutron Skylark Contour CT-600P Incandescent Leading 600 1 12 Lutron

Compatible Part Numbers



4" Recessed Downlight

CR4T-790L-27K-12-E26GU24 CR4T-790L-30K-12-E26GU24 CR4T-790L-35K-12-E26GU24 CR4T-790L-40K-12-E26GU24

*The presence of a dimmer on this chart is not a guarantee or warranty of the compatibility of the LED bulb in any particular installation. Absence of a dimmer from this chart does not imply incompatibility.

Bulbs Per Dimmer

Please reference the dimmer manufacturer's instructions for installation and further information.

Works With
May produce some
flicker or shimmer.
Minimum adjustment
to dimming level may

be required.

No audible noise.

Manufacturer	Series	Number	Load Type	Cut Edge	(W)	min	max
Leviton	Illumatech	IPE041	ELV	Trailing	300	1	18

Phase

Rating

Part