

# PAR38 Series

Cree Professional Series LED Lamps

## Product Description


At Cree®, we believe in better lighting. Better light is beautiful light. But it's more than just beautiful. It is light that makes you feel more productive, more relaxed and safer. Better light changes everything. That's why the new and improved 90+ CRI Cree Professional Series LED bulbs feature high color rendering that enhances your space and makes the colors of your decor appear vibrant, richer and more natural –true colors the way they are meant to be experienced.

The ENERGY STAR certified, California complaint Cree Professional Series PAR38 LED bulb is a higher lumen solution ideal for use indoors in a track or recessed can, or outdoors in security or landscaping lighting. Delivering up to 1,500 lumens of 2700K, 3000K, or 4000K light, halogen-like light white using up to 19 watts, the Cree PAR38 LED bulb is available in multiple beam angles for different applications. It is fully dimmable and designed to last 25,000 or 50,000 hours.


## Performance Summary

<b>Beam Spreads:</b> 15° Spot, 25° Narrow Flood, 40° Flood
<b>Lamp Delivered Light Output:</b> 120W Replacement: 1,330 -1,370 Lumens; 150W Replacement: 1,500 Lumens
<b>Input Power:</b> 120W Replacement: 16.5 watts; 150W Replacement: 19 watts
<b>CRI:</b> >90
<b>CCT:</b> 2700K, 3000K, 4000K
<b>Limited Warranty*:</b> 5 years Commercial use
<b>Lifetime:</b> 120W Replacement: Designed to last at least 50,000 hours; 150W Replacement: Designed to last at least 25,000 Hours
<b>Dimming:</b> Dimmable to 5% with select dimmers
ENERGY® Star Certified 150W Only, 120W (May 2019); CEC California Title 20 Compliant
Can be ordered in Single Lamp Cartons (Master Carton Quantity = 12)

120W



150W



## Ordering Information

Example: PAR38-120W-P1-30K-40FL-E26-U1

PAR38		P1				E26		U1
Product	Watt Equivalent	Series	CCT	Beam Spread	Voltage	Base	CRI	Packaging Options
<b>PAR38</b>	<b>120W</b> 120 Watt, 1,300 - 1,370 Lumens CBCP = 15°: 16,000 Candelas, 25°: 6,800 - 7,300 Candelas, 40°: 2,500 - 3,000 Candelas <b>150W</b> 1500 lumens CBCP = 3,360 Candelas	<b>P1</b> Professional Series 1 <sup>st</sup> Generation	<b>27K</b> 2700K (120W Only) <b>30K</b> 3000K <b>40K</b> 4000K (120W, 40° Flood Only)	<b>15SP</b> 15° Spot (120W Only) <b>25NF</b> 25° Narrow Flood (120W Only) <b>40FL</b> 40° Flood	<b>Blank</b> 120 Volt	<b>E26</b> Edison Base	<b>Blank</b> >90 CRI	<b>U1 Single-Lamp Carton</b> Master Carton = 12 Single-Lamp Cartons



Rev. Date: V3 05/09/2019



## PAR38 Pro Series LED Lamps

### Product Specifications

#### CONSTRUCTION & MATERIALS

- PAR38 120W design weighing 7.8 ounces (221g); 150W design weighing 7.2 ounces (204g)
- E26 Medium standard screw type base
- Bulb meets ANSI standards for PAR38 dimensions
- Mercury free
- **Dimensions:** 120W Replacement: 5.6" H x 4.7" W x 4.7" D (Single Lamp Carton); 11" H x 14.5" W x 9.7" D (Master Carton); 150W Replacement: 6.5" H x 4.9" W x 4.9" D (Single Lamp Carton); 7.2" H x 15.4" W x 20.4" D (Master Carton)


#### OPTICAL SYSTEM

- Plastic lens offers increased optical spread

#### ELECTRICAL SYSTEM

- **Power Factor :** > 0.9 nominal
- **Input Voltage:** 120V, 60Hz
- **Dimming:** Dimmable to 5% with select dimmers.
- **Operating Temperature Range:** -25°C - +45°C (-13°F - +113°F)

#### REGULATORY & VOLUNTARY QUALIFICATIONS

- cULus Listed
- Suitable for wet locations where exposed directly to weather
- Suitable for use in enclosed light fixtures. Lifetime may be reduced if used in air tight enclosures or in insulated ceiling air tight (ICAT) recessed downlight enclosures
- Meets FCC Part 15, Subpart B, Class B standards for conducted and radiated emissions
- ENERGY STAR® Certified:  
120W Replacement ENERGY STAR Certification Expected May 2019,  
150W Replacement ENERGY STAR Certified
- RoHS compliant. Consult factory for additional details
- CEC California Title 20 Compliant
-  **CA RESIDENTS WARNING:** Cancer and Reproductive Harm – [www.p65warnings.ca.gov](http://www.p65warnings.ca.gov)

Ordering Number	Single-Lamp Carton UPC	Description	Bulb Type	Watts	CCT	Single-Lamp Cartons per Master Carton	Master Carton ITF-14	Total Lamps per Master Carton	Master Cartons per Pallet Qty	CRI	CBCP	Lumens	Rated Life (Hrs)
PAR38-120W-P1-27K-40FL-E26-U1	849665026563	120W Soft White 40° Flood, PAR38 Equivalent	PAR38	16.5	2700K	12	10849665026560	12	40	>90	2,500	1,330	50,000
PAR38-120W-P1-27K-25NF-E26-U1	849665026570	120W Soft White 25° Narrow Flood, PAR38 Equivalent	PAR38	16.5	2700K	12	10849665026577	12	40	>90	6,800	1,330	50,000
PAR38-120W-P1-27K-15SP-E26-U1	849665026587	120W Soft White 15° Spot, PAR38 Equivalent	PAR38	16.5	2700K	12	10849665026584	12	40	>90	16,000	1,330	50,000
PAR38-120W-P1-30K-40FL-E26-U1	849665026594	120W Bright White 40° Flood, PAR38 Equivalent	PAR38	16.5	3000K	12	10849665026591	12	40	>90	3,000	1,370	50,000
PAR38-120W-P1-30K-25NF-E26-U1	849665026600	120W Bright White 25° Narrow Flood, PAR38 Equivalent	PAR38	16.5	3000K	12	10849665026607	12	40	>90	7,300	1,370	50,000
PAR38-120W-P1-30K-15SP-E26-U1	849665026617	120W Bright White 15° Spot, PAR38 Equivalent	PAR38	16.5	3000K	12	10849665026614	12	40	>90	16,000	1,370	50,000
PAR38-120W-P1-40K-40FL-E26-U1	849665026624	120W Daylight 40° Flood, PAR38 Equivalent	PAR38	16.5	4000K	12	10849665026621	12	40	>90	3,000	1,370	50,000
PAR38-150W-P1-30K-40FL-E26-U1	849665023319	150W Replacement Bright White 40° Flood PAR38	PAR38	19	3000K	12	10849665023316	12	30	>90	3,360	1,500	25,000