





FEATURES

- Advanced heat sink design makes fixture light in weight and better at heat dissipation
- Well suited light distribution for parking lot and stadium lighting
- Corrosion-proof with durable die-cast aluminum alloy body
- Suitable for wet locations
- IP65 Rated

PLT-50184	4000	5960	50	120-277	No	Knuckle	50,000	3 years
SKU#	Kelvin	Lumens	Wattage	Voltage	DLC?	Mounting	Life Hours	Warranty

ADDITIONAL PHOTOS









FEATURES

SPECIFICATIONS

- Longer life span than Metal Halide
- Minimizes maintenance checks
- Lightweight, compact design
- Seoul Semiconductor LEDs

TYPICAL APPLICATIONS

- Security Lighting
- Pedestrian Lighting

WARRANTY

WARRANTY 3 Years

PERFORMANCE

5960 Lumen Output 50W Power Consumption 5000K Color Temperature 50000 hrs Lumen Maintenance 120-277 Input Voltage

ENVIRONMENTAL

IP65 Rating - Wet Location -35^+50°C Operating Temperature 10%-95% Humidity

PHYSICAL

Dimensions (8.85 in. \times 5.98 in. \times 2.99 in.) Weight 2.2 lbs.

Yoke Style Mounting Options Housing: Die-Casting Aluminum