PL V 10W BYP TITANIUM LED SERIES







PRO

- Built-in universal voltage driver Bypass installation
- Ompatible with G24d, GX24d, G24d & GX24d bases
- Innovative round design
- Exceptional efficacy 102 LPW
- Available in 2700K, 3000K, 3500K & 4000K CCT
















PL PRODUCT FEATURES

BYPass Installation

This PL V lamp is not compatible with magnetic or electronic ballasts and requires bypassing the ballast during installation. The lamp runs directly off line voltage to eliminate compatibility problems, incidental power loss, lifetime issues, and maintenance costs associated with ballasts.





DESIGNED FOR HORIZONTAL APPLICATIONS




PL V 10W BYP TITANIUM LED SERIES










Base: G24d, GX24d, G24q &

GX24q (2/4-pin CFL)

Voltage: 120-277V

Dimmable: No PF: 0.9

Lifetime (L70): 50,000 hrs Weight: 0.21lb / 95g



SPECIFICATIONS

Model	Product	Power (W)	сст	CRI (typ.)	Lumens	LPW	Beam Angle
10PLV/827/BYP	28362	(10)	Soft White 2700K	82	950	95	(120°)
10PLV/830/BYP	28363	10	Warm White 3000K	82	1000	100	120°
10PLV/835/BYP	28364	10	Neutral White 3500K	82	1000	100	120°
10PLV/840/BYP	28365	10	Cool White 4000K	82	1020	102	120°

^{*} Suitable for damp locations. Not for use where directly exposed to weather or water ** Not intended for use in enclosed fixtures *** Full installation guide and more details available on website