Features & Specifications

INTENDED USE – This PLT LED shop light fixture combines a traditional linear design with high-output LED chips to provide an energy-efficient, low maintenance fixture suitable for replacing existing fluorescent strip light fixtures. This medium body fixture is for interior warehouse, retail, and utility areas requiring general illumination in a commercial quality strip configuration.

CONSTRUCTION – Rugged 24 Gauge cold-rolled steel housing with high gloss baked enamel paint for lasting durability. Wiring knockouts are provided on back and end of housing. End plate doubles as coupler for continuous row mounting.

OPTICS – Two integrated LED arrays emit 2000 Lumens of output each, for a total of 4000 Lumens maintained at 4000K for 50,000 hours of use. Each LED ray features a rounded lens cover that creates the appearance of tubes. Fixture uses 40 Watts and has a CRI of 80.

ELECTRICAL – Does not include ballast. Input voltage of 120 VAC. Includes occupancy sensor.

INSTALLATION – Designed for surface, chain hung, or double stem mounting. See Installation Instruction PDF for more information.

LISTINGS – ETL Certified to safety standards. Rated for dry locations. IP-40 Rated.

WARRANTY – 3-year warranty. PLT products that are damaged or defective will be repaired or replaced at PLT's choosing for a period of 3 years. Contact 1-800-624-4488 for more information.



Dimensions:

Height: 1.8 in. Width: 5.14 in. Length: 47.5 in.





SKU #	KELVIN	LUMENS	CRI	WATTAGE	LIFE HOURS	MOUNTING	VOLTAGE	WARRANTY
PLT-11668	4000K	4000	80	40W	50,000	CHAIN/SURFACE	120	3 YEARS