


Model: 808

120V Track MR16 Luminaire

WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

Low Voltage luminaire with die-cast aluminum construction and swivel yoke for precise aiming.

FEATURES

• Available with LED lamp option

- Swivel yoke for easy aiming
- 350° horizontal rotation and 90° vertical tilt
- Recessed lamp position and baffle for minimal glare
- Clear lens included (Halogen version)
- Dimmable
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Construction: Die-cast aluminum track head with polycarbonate transformer case and track adapter. Bi-pin ceramic socket for MR16 lamp.

Finish: Available in Black (BK), Dark Bronze (DB) and White (WT).

Transformer: LED Version - 1W minimum load.
Halogen Version - 20W minimum load (1W minimum load available. Consult factory for more details).

Lamp: 808 model uses 12V MR16, 50W max lamp (not included).
808L model uses 12V MR16, 75W max (not included).
808LED model uses a 12V, 8W MR16 LED lamp (included).
450 lumens, 3000K CCT, 25,000 hour rated life, CRI: 85.

Dimming: With electronic low voltage (ELV) dimmer, LED lamp dims to 10%; Halogen lamp dims to 1%.

Standards: UL & CUL Listed.

ORDER NUMBER

System	Model #	Power	Lamp	Finish
LHT L Track	808LED	8W	LED	BK Black
HHT H Track	808	50W	Halogen	DB Dark Bronze
JHT JJ2 Track	808L	75W	Halogen	WT White

- -

Example: **LHT-808LED-DB**

FINISHES

BK	DB	WT

ACCESSORIES

Color Lens	LENS-16-	AMB BLU GRN RED YEL	Amber Blue Green Red Yellow	UV Filter Frosted Lens Spread Lens Beam Elongating Lens Honeycomb Louver	LENS-16-UVF LENS-16-FR LENS-16-SPR LENS-16-BEL LENS-16-HCL
------------	-----------------	---------------------------------	---	--	---

WAC Lighting

www.waclighting.com

Phone (800) 526.2588 • Fax (800) 526.2585

Headquarters/Eastern Distribution Center

44 Harbor Park Drive • Port Washington, NY 11050

Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center

1750 Archibald Avenue • Ontario, CA 91760

Phone (800) 526.2588 • Fax (800) 526.2585