

# ULTRA Glass LED A-line Lamps

25,000 Hour Life



SYLVANIA offers an extensive portfolio of Classic LED A-line lamps. All lamps have the look and feel of traditional incandescent lamps, while utilizing all the benefits and innovation of LEDs, such as energy savings, long life, and brilliant illumination, while promoting job growth and supporting the U.S. economy.

Assembled in USA ULTRA LED A-line lamps are direct replacements for 40/60/75/100W incandescent lamps and are available in a warm white 2700K and a cool white 5000K.

All lamps are dimmable, have an excellent color rendering of 80+, and are rated up to 25,000 hours (L<sub>70</sub>) of life. They are also ENERGY STAR certified for increased utility rebates, making them ideal for a variety of residential and commercial applications.

## Key Features & Benefits

- Lamps Assembled in the USA
- Full glass housing manufactured in the USA
- Look and feel of traditional lamps while utilizing all the benefits of LEDs
- Available in 2700K and 5000K color temperatures
- Indoor and outdoor rated (UL Damp)
- Mercury and lead free
- Dimmable
- ENERGY STAR® certified
- Long rated life of 25,000 hours (L<sub>70</sub>)
- No warm up time, instant on with full light output and stable color



## Product Offering

| Ordering Abbreviation | Wattage | Color Temperature | Typical Lumens |
|-----------------------|---------|-------------------|----------------|
| LED4.5A19             | 4.5     | 2700K, 5000K      | 450            |
| LED6.519              | 6.5     | 2700K, 5000K      | 800            |
| LED9A21               | 9       | 2700K, 5000K      | 1100           |
| LED11A21              | 11      | 2700K, 5000K      | 1600           |

## Application Information

### Applications

- Downlights
- Pendant fixtures
- Table/floor lamps
- Wall sconces

### Market Segments

- Hospitality
- Office
- Residential
- Retail

### Application Notes

1. Operating temperature range between -20°C and +45°C (-4°F and +113°F)
2. Not for use with emergency light fixtures or exit lights
3. Suitable for damp locations



## Specification Data

|             |      |
|-------------|------|
| Catalog #   | Type |
| Project     |      |
| Comments    |      |
| Prepared by |      |

## Ordering Information


| Item Number | Ordering Abbreviation   | Wattage (W) | Base Type | Replaces | Input Voltage (V) | Average Rated Life (hrs.) | CCT   | Typical Lumens (lm) | CRI | Bulb Finish | ENERGY STAR® |
|-------------|-------------------------|-------------|-----------|----------|-------------------|---------------------------|-------|---------------------|-----|-------------|--------------|
| 74963       | LED4.5A19/DIM/O/827/RP4 | 4.5         | Medium    | 40W      | 120               | 25,000                    | 2700K | 450                 | 82  | Frosted     | Yes          |
| 74964       | LED4.5A19/DIM/O/827/RP  | 4.5         | Medium    | 40W      | 120               | 25,000                    | 2700K | 450                 | 82  | Frosted     | Yes          |
| 74965       | LED4.5A19/DIM/O/850/RP4 | 4.5         | Medium    | 40W      | 120               | 25,000                    | 5000K | 450                 | 82  | Frosted     | Yes          |
| 74966       | LED4.5A19/DIM/O/850/RP  | 4.5         | Medium    | 40W      | 120               | 25,000                    | 5000K | 450                 | 82  | Frosted     | Yes          |
| 74967       | LED6.5A19/DIM/O/827/RP4 | 6.5         | Medium    | 60W      | 120               | 25,000                    | 2700K | 800                 | 82  | Frosted     | Yes          |
| 74968       | LED6.5A19/DIM/O/827/RP  | 6.5         | Medium    | 60W      | 120               | 25,000                    | 2700K | 800                 | 82  | Frosted     | Yes          |
| 74969       | LED6.5A19/DIM/O/850/RP4 | 6.5         | Medium    | 60W      | 120               | 25,000                    | 5000K | 800                 | 82  | Frosted     | Yes          |
| 74970       | LED6.5A19/DIM/O/850/RP  | 6.5         | Medium    | 60W      | 120               | 25,000                    | 5000K | 800                 | 82  | Frosted     | Yes          |
| 74971       | LED9A21/DIM/O/827/RP4   | 9           | Medium    | 75W      | 120               | 25,000                    | 2700K | 1100                | 82  | Frosted     | Yes          |
| 74972       | LED9A21/DIM/O/827/RP    | 9           | Medium    | 75W      | 120               | 25,000                    | 2700K | 1100                | 82  | Frosted     | Yes          |
| 74973       | LED9A21/DIM/O/850/RP4   | 9           | Medium    | 75W      | 120               | 25,000                    | 5000K | 1100                | 82  | Frosted     | Yes          |
| 74974       | LED9A21/DIM/O/850/RP    | 9           | Medium    | 75W      | 120               | 25,000                    | 5000K | 1100                | 82  | Frosted     | Yes          |
| 74975       | LED11A21/DIM/O/827/RP4  | 11          | Medium    | 100W     | 120               | 25,000                    | 2700K | 1600                | 82  | Frosted     | Yes          |
| 74976       | LED11A21/DIM/O/827/RP   | 11          | Medium    | 100W     | 120               | 25,000                    | 2700K | 1600                | 82  | Frosted     | Yes          |
| 74977       | LED11A21/DIM/O/850/RP4  | 11          | Medium    | 100W     | 120               | 25,000                    | 5000K | 1600                | 82  | Frosted     | Yes          |
| 74978       | LED11A21/DIM/O/850/RP   | 11          | Medium    | 100W     | 120               | 25,000                    | 5000K | 1600                | 82  | Frosted     | Yes          |

## Ordering Guide

|            |            |            |          |            |          |                 |          |          |           |          |             |
|------------|------------|------------|----------|------------|----------|-----------------|----------|----------|-----------|----------|-------------|
| <b>LED</b> | <b>4.5</b> | <b>A19</b> | <b>/</b> | <b>DIM</b> | <b>/</b> | <b>O</b>        | <b>/</b> | <b>8</b> | <b>27</b> | <b>/</b> | <b>RP4</b>  |
| LED        | Wattage    | Lamp Type  |          | Dimmable   |          | Omnidirectional |          | CRI      | CCT       |          | Retail Pack |

## Lamp Dimensions

|           | (A)<br>MOL<br>inches (mm) | (B)<br>Diameter<br>inches (mm) |
|-----------|---------------------------|--------------------------------|
| LED4.5A19 | 4.4 (112)                 | 2.36 (60)                      |
| LED6.5A19 | 4.4 (112)                 | 2.36 (60)                      |
| LED9A21   | 5.17 (131.4)              | 2.56 (65)                      |
| LED11A21  | 5.17 (131.4)              | 2.56 (65)                      |



LEDVANCE LLC  
 200 Ballardvale Street  
 Wilmington, MA 01887 USA  
 Phone 1-800-LIGHTBULB (1-800-544-4828)  
[www.sylvania.com](http://www.sylvania.com)

SYLVANIA and LEDVANCE are registered trademarks.  
 All other trademarks are those of their respective owners.  
 Licensee of product trademark SYLVANIA in general lighting.  
 Specifications subject to change without notice.

[/sylvania](https://twitter.com/sylvania) [/sylvania](https://facebook.com/sylvania)

