

Project Name:	Type:
Part Number:	Date:

A LAMP FAMILY

FEATURES

- Suitable to replace 60W, 75W, 100W Incandescent
- High CRI and R values (R9 57, R13 95) deliver richer reds and healthier skin tones
- Tight LED binning for consistent CCT across all lamps
- Smooth dimming with most forward and reverse phase dimmers*
- Suitable for use in totally enclosed fixtures**
- Suitable for use in damp locations
- Operating temperature: -4°F / -20°C to +95°F / +35°C
- Rated Lifetime (L70): 25,000hrs
- 5 year limited warranty for 60W & 75W equivalents
- 3 year limited warranty for 100W equivalents



SPECIFICATIONS


Product	Model	Equiv.	Wattage (W)	CCT	Lumens	Efficacy (LPW)	Input Voltage	Beam Angle	CRI	Dim.*	Power Factor	Base	Fixture Rating	Cert.
98559	9A19DIM/927	60W	9	2700K	800	89	120V	240°	92	Yes	0.9	E26	Enclosed	ES / JA8 / T20
98560	9A19DIM/930	60W	9	3000K	820	91	120V	240°	92	Yes	0.9	E26	Enclosed	ES / T20
98561	9A19DIM/940	60W	9	4000K	860	96	120V	240°	92	Yes	0.9	E26	Enclosed	ES / T20
98565	9A19DIM/927/GU24/R	60W	9	2700K	800	89	120V	240°	92	Yes	0.9	GU24	Enclosed	ES / JA8 / T20
98562	9A19/927/277V	60W	9	2700K	800	89	120-277V	240°	92	No	0.9	E26	Enclosed	ES / T20
98563	9A19/930/277V	60W	9	3000K	820	91	120-277V	240°	92	No	0.9	E26	Enclosed	ES / T20
98564	9A19/940/277V	60W	9	4000K	860	96	120-277V	240°	92	No	0.9	E26	Enclosed	ES / T20
98141	11A19DIM/927	75W	11	2700K	1100	100	120V	240°	92	Yes	0.9	E26	Enclosed	ES / T20
98142	11A19DIM/930	75W	11	3000K	1150	105	120V	240°	92	Yes	0.9	E26	Enclosed	ES / T20
98143	11A19DIM/940	75W	11	4000K	1200	109	120V	240°	92	Yes	0.9	E26	Enclosed	ES / T20
98147	15A21DIM/927/N	100W	15	2700K	1600	107	120V	240°	92	Yes	0.9	E26	Enclosed	ES / JA8 / T20
98148	15A21DIM/930/N	100W	15	3000K	1650	110	120V	240°	92	Yes	0.9	E26	Enclosed	ES / T20
98149	15A21DIM/940/N	100W	15	4000K	1700	113	120V	240°	92	Yes	0.9	E26	Enclosed	ES / T20

* This lamp might not be compatible with all dimmers. Please visit www.greencreative.com for compatibility information.




A LAMP FAMILY


DIMENSIONS & WEIGHT



Model	Base	MOL	Dia.	Weight
9A19DIM/xxx	E26	4-1/2"	2-3/8"	0.12lb
9A19/xxx/277V	E26	4-1/2"	2-3/8"	0.12lb
11A19DIM/xxx	E26	4-1/2"	2-3/8"	0.12lb



Model	Base	MOL	Dia.	Weight
9A19DIM/xxx/GU24/R	GU24	4-3/16"	2-3/8"	0.11lb



Model	Base	MOL	Dia.	Weight
15A21DIM/xxx/N	E26	5-7/16"	3"	0.23lb

** MINIMUM COMPARTMENT DIMENSIONS (FOR ENCLOSED FIXTURES)

Model	Diameter	Height
9A19DIM/xxx	6"	8-1/2"
9A19DIM/xxx/GU24/R	6"	8-1/2"
9A19/xxx/277V	6"	8-1/2"
11A19DIM/xxx	6"	8-1/2"
15A21DIM/xxx/N	6"	8-1/2"

Installing lamp in a fixture that does not have the minimum compartment dimensions will void the warranty and could cause product failures.