



## FEATURES

- Bypasses ballast to connect to 120-277 line voltage, eliminating compatibility issues
- Includes 6kV surge protection to prevent against electricity spikes
- IP64 rated, dust-tight and water resistant
- Provides an efficient replacement for 400W HID fixtures
- Emits light at an all-encompassing 360 degree beam angle
- DLC Part Number ®: PLTBA134

SKU#	Kelvin	Lumens	Base	Wattage	Voltage	DLC?	Mounting	Life Hours	Warranty
PLT-11689	4000	16,800	Mogul	120	120-277	Yes	Vertical	50,000	5 Years

## ADDITIONAL PHOTOS



12.24"

## FEATURES

- Direct line voltage 120-277V - Ballast Bypass
- Replaces 400W HID fixtures
- 6kV surge protection

## SPECIFICATIONS

DIMMABLE .....	NO
DLC LISTED .....	YES
SAFETY RATING .....	UL
CRI .....	80
COLOR .....	COOL WHITE
COLOR TEMPERATURE .....	4000K
LIFE HOURS .....	50,000
WATTAGE .....	120 WATTS
LUMENS .....	16,800
VOLTAGE .....	120-277
FINISH.....	WHITE
HOUSING.....	ALUMINUM
MOUNTING .....	VERTICAL: BASE UP, BASE DOWN
LENGTH .....	4.84 IN.
HEIGHT .....	12.24 IN.
WIDTH.....	4.84 IN.
WEIGHT .....	4.89 LBS.

## TYPICAL APPLICATIONS

- Schools, Factories, Hotels
- Offices, Conference Rooms
- Hospitals

## WARRANTY

**Warranty**

**5 Years**

When retrofitting HID fixtures with LED lights, ballast must be bypassed if present. If used in an enclosed fixture, the enclosed fixture must be 16.14" wide x 16.14" deep x 11.81" high (410mm x 410mm x 300 mm) or larger. VERTICAL INSTALLATION (± 20°) ONLY

## WIRE DIAGRAM

### Replacing HPS/HID Lamp

