

SCREW-IN
RETROFITS



A21/23 HIGH OUTPUT



safe for use →
in enclosed
fixtures



- Frosted design to reduce glare.
- 360° light output for optimal performance.
- Available in 3000K, 4000K & 5000K
- Pretested & potted drivers are burnt in 3x prior to shipping and protected against vibration & moisture.
- Engineered to work efficiently in enclosed fixtures & damp environments.
- Protected against insects & dust.
- 8017-G2 dimmable model available.
- LED-8017-G2-DIM is 120V only.

ALSO WORKS ON 208V & 240V	INSTALL METHOD	MEDIUM + MOGUL BASE	VERTICAL MOUNTING	CRI	OPERATING TEMP	ENCLOSED FIXTURES	50,000hrs RATED LIFE	INGRESS PROTECTION	






PART #	UPC	REPLACES	WATTAGE	LUMENS	COLOR (K)*	BASE
LED-8015E50-G2	844006035983	70W	14W	1960	5000K	E26
LED-8017E50-G2	844006036010	100W	20W	2740	5000K	E26
LED-8017E50-G2-DIM	844006052232	100W	20W	2660	5000K	E26
LED-8018E50-G2	844006036041	150W	25W	3340	5000K	E26
LED-8018M50-G2	844006036072	150W	25W	3575	5000K	EX39
LED-8019M50-G2	844006036102	175W	35W	4690	5000K	EX39

* additional color temperatures shown on page 2





A21/23 HIGH OUTPUT



PART #	UPC	REPLACES (INC)	REPLACES (HID)	WATTAGE	LUMENS	CCT	BASE	ENERGY STAR	DLC CODES
LED-8015E30-G2	844006035969	100W	70W	14W	1792	3000K	E26	✓	N/A
LED-8015E40-G2	844006035976	100W	70W	14W	1918	4000K	E26	✓	N/A
LED-8015E50-G2	844006035983	100W	70W	14W	1960	5000K	E26	✓	N/A
LED-8017E30-G2	844006035990	150W	100W	20W	2620	3000K	E26	✓	N/A
LED-8017E40-G2	844006036003	150W	100W	20W	2720	4000K	E26	✓	N/A
LED-8017E50-G2	844006036010	150W	100W	20W	2740	5000K	E26	✓	N/A
LED-8017E30-G2-DIM	844006052218	150W	100W	20W	2620	3000K	E26	✓	N/A
LED-8017E40-G2-DIM	844006052225	150W	100W	20W	2720	4000K	E26	✓	N/A
LED-8017E50-G2-DIM	844006052232	150W	150W	20W	2740	5000K	E26	✓	N/A
LED-8018E30-G2	844006036027	200W	150W	25W	3160	3000K	E26	✓	N/A
LED-8018E40-G2	844006036034	200W	150W	25W	3350	4000K	E26	✓	N/A
LED-8018E50-G2	844006036041	200W	150W	25W	3340	5000K	E26	✓	N/A
LED-8018M30-G2	844006036058	200W	150W	25W	3375	3000K	EX39	N/A	PLYYO2FRL1TZ
LED-8018M40-G2	844006036065	200W	150W	25W	3525	4000K	EX39	N/A	PLJ38NJP57SW
LED-8018M50-G2	844006036072	200W	150W	25W	3575	5000K	EX39	N/A	PL3PUZI7KO7Y
LED-8019M30-G2	844006036089	300W	175W	35W	4400	3000K	EX39	N/A	PLFD10SWG40S
LED-8019M40-G2	844006036096	300W	175W	35W	4400	4000K	EX39	N/A	PLZ89EO4KDCG
LED-8019M50-G2	844006036102	300W	175W	35W	4690	5000K	EX39	N/A	PLGAMPK6VXAH