

HOTEL Elements

by TCP

LED Flood Light Product Specifications



TCP's LED Flood Light is a robust 50 watt flood designed for outdoor lighting. An efficient alternative to HID, these flood lights deliver bright uniform light while providing energy savings. A long 50,000 hour rated life significantly decreases maintenance labor and material costs over the life of the fixture.

The robust die-cast aluminum housing incorporates an impact resistant acrylic lens. The flood light has a yoke or adjustable 1/2" knuckle mount for easy installation or retrofit of traditional luminaires.

Reasons to choose the LED Flood Light from TCP

- Long 50,000 hour rated life reduces maintenance and replacement costs
- Die-cast aluminum housing with impact resistant acrylic lens
- Knuckle and Yoke mounting options for easy installation or retrofits
- Delivers bright, uniform light

Ideal Applications

- Landscape Lighting
- Wall Wash
- Sign Lighting
- Accent Lighting

Applications

This product can be used in many outdoor applications including security lighting, wall wash, sign lighting and accent lighting. The knuckle or yoke mount options provide a versatile array of mounting options.

Construction

- Die-cast aluminum housing
- Impact resistant acrylic lens
- Durable bronze powdercoat
- 1/2" knuckle mount or yoke mount
- Operating Temperature: -40°C to 55°C.


Electrical

- cULus wet location rated
- Easily access wiring for quick installation
- System rated for long 50,000 hour life
- Efficiently delivers up to 125 LPW

Optics

- Prismatic acrylic lens
- Delivers bright, white light and excellent uniformity

Dimensions



Listings

cULus Listed – wet location rated
RoHS Compliant

Warranty

Five year limited warranty against defects in manufacturing.

LED Flood Light Available Part Numbers

| Item # | Description | LUMENS | WATTAGE | LPW | VOLTAGE | CCT | CRI | LIFE (HRS) | L (IN) | H (IN) | W (IN) |
|--------------|--|--------|---------|-----|-----------|-------|-----|------------|--------|--------|--------|
| FLKUA3W40KBR | Small Flood Knuckle UNI 6250L Wide Beam 4K | 6,250 | 50 | 125 | 120 - 277 | 4000K | >70 | 50,000 | 7.5 | 4.5 | 2.25 |
| FLKUA3W50KBR | Small Flood Knuckle UNI 6250L Wide Beam 5K | 6,250 | 50 | 125 | 120 - 277 | 5000K | >70 | 50,000 | 7.5 | 4.5 | 2.25 |
| FLYUA3W40KBR | Small Flood Yoke UNI 6250L Wide Beam 4K | 6,250 | 50 | 125 | 120 - 277 | 4000K | >70 | 50,000 | 7.5 | 4.5 | 2.25 |
| FLYUA3W50KBR | Small Flood Yoke UNI 6250L Wide Beam 5K | 6,250 | 50 | 125 | 120 - 277 | 5000K | >70 | 50,000 | 7.5 | 4.5 | 2.25 |