



## FEATURES

- USA approved LM-80 SMD
- UL LM79 certified
- Input Voltage: 120-277 VAC 50/60Hz
- THD:<20%(at 277V)
- High lumen output, high efficiency, energy saving up to 50%
- Standard Warranty: 5 Years
- Standard Lifetime: Designed to L70 minimum 50,000 hours
- UL File Number - E485624






**50% ENERGY EFFICIENCY & LONG LIFE**

TYPICAL PAYBACK OF 1 - 3 YEARS

	Voltage	DLC?	Mounting	Life Hours	Warranty
<b>LEDF-10156 5000 3800 2X2 36</b>	<b>120-277</b>	<b>NO</b>	<b>CEILING</b>	<b>50000</b>	<b>5 years</b>

## ADDITIONAL PHOTOS



## FEATURES

- Opaque Lens
- Lightweight design
- LED driver included

## TYPICAL APPLICATIONS

- Schools, Factories, Hotels
- Office, Conference Rooms
- Hospitals


## WARRANTY

Warranty

5 Years

## SPECIFICATIONS

Dimmable .....	Yes
DLC Listed .....	No
Safety Rating .....	UL
CRI .....	80
Color.....	Cool White
Color Temperature.....	5000 Kelvin
Life Hours .....	50,000
Wattage .....	36 Watt
Lumens.....	3800
Voltage .....	120-277
Finish.....	White
Housing .....	Aluminum
Mounting .....	Ceiling Grid Mount/Suspended
Lens .....	Opaque
Length .....	23.7 in.
Height .....	0.35 in.
Width .....	23.7 in.
Weight.....	7.01 lbs.
Warranty.....	5 Years



## PHOTOMETRICS

