



FEATURES

- USA approved LM-80 SMD
- UL LM79 certified
- Input Voltage: 100-277 VAC 50/60Hz
- THD:<20%(at 277V)
- High lumen output, high efficiency, energy saving up to 50%
- Standard Warranty: 5 Years
- Standard Lifetime: Designed to L70 minimum 50,000 hours
- UL# E485624




50% ENERGY EFFICIENCY & LONG LIFE

TYPICAL PAYBACK OF 1 - 3 YEARS

SKU #	Kelvin	Lumens	Size	Wattage	Voltage	DLC?	Mounting	Life Hours	Warranty
LEDF-10164	5000	6250	2X4	50	100-277	NO	CEILING	50000	5 years

ADDITIONAL PHOTOS



FEATURES

- Opaque Lens
- Lightweight design
- LED driver included


TYPICAL APPLICATIONS

- Schools, Factories, Hotels
- Office, Conference Rooms
- Hospitals

WARRANTY

Warranty

5 Years



SPECIFICATIONS

Dimmable	Yes
DLC Listed	No
Safety Rating	UL
CRI	80
Color	Stark White
Color Temperature	5000 Kelvin
Life Hours	50,000
Wattage	50 Watt
Lumens	6250
Voltage	100-277
Finish	White
Housing	Aluminum
Mounting	Ceiling Grid Mount/Suspended
Lens	Opaque
Length	47.75 in.
Height	1.9 in.
Width	23.7 in.
Weight	14 lbs.
Warranty	5 Years

PHOTOMETRICS

