





FEATURES

- Well suited light distribution for parking lot and roadway lighting
- Advanced heat sink design makes fixture light in weight and better at heat dissipation
- Suitable for Wet Location
- Beautiful appearance, using Samsung LED chips and high quality driver
- IP65 Rated
- ETL Listed





87% ENERGY EFFICIENCY & LONG LIFE 60% MORE ENERGY EFFICIENT THAN STANDARD HID LAMPS TYPICAL PAYBACK OF 1 - 3 YEARS

SKU #	Kelvin	Lumens	Wattage	Voltage	DLC?	Mounting	Life Hours	Warranty
PLT-10826-S	5000	12500	100	120-277	NO	STRAIGHT	50000	5 years

ADDITIONAL PHOTOS







FEATURES

SPECIFICATIONS

- Longer life span than Metal Halide
- Minimizes Maintenance Checks
- Type III Light Distribution

TYPICAL APPLICATIONS

- Security Lighting
- Pedestrian Lighting

WARRANTY

WARRANTY 5 Y

5 Years

PERFORMANCE

Samsung LED Chip 12500 Lumen Output (IES) 100W Power Consumption 125 Im/W Efficacy (IES) 5000K Color Temperature >50000 hrs Lumen Maintenance 120-277 Input Voltage 100W Power Factor

ENVIRONMENTAL

IP65 Rating - Wet Location -40~+45°C Operating Temperature -40~+80°C Storing Temperature 10%-95% Humidity

PHYSICAL

Dimensions (18.87 in. x 12.99 in. x 2.36 in.) Weight 19 lbs. Straight Arm Mounting Options Housing: Die-Casting Aluminum

Mounting Arm for Square Pole

