

# LED PANEL



## FEATURES


- USA approved LM-80 SMD
- Input Voltage: 120-277 VAC 50/60Hz
- THD:<20%(at 277V)
- High lumen output, high efficiency, energy saving up to 60%
- Standard Warranty: 5 Years
- Standard Lifetime: Designed to L70 minimum 36,000 hours



**50% ENERGY EFFICIENCY & LONG LIFE**  
60% MORE ENERGY EFFICIENT THAN STANDARD HID LAMPS  
TYPICAL PAYBACK OF 1 - 3 YEARS

SKU #	Kelvin	Lumens	Size	Wattage	Voltage	DLC?	Mounting	Life Hours	Warranty
PLT-10535	5000	5200	2X4	52	120-277	No	CEILING	36,000	5 years

## ADDITIONAL PHOTOS



## FEATURES

- Opaque Lens
- Lightweight design
- LED driver included

## TYPICAL APPLICATIONS

- Hotels, Schools, Factories
- Office, Hospitals

## WARRANTY

Warranty

5 Years

## SPECIFICATIONS

Dimmable .....	Yes
DLC Listed .....	No
Safety Rating .....	UL
CRI .....	80
Color .....	Stark White
Color Temperature .....	5000 Kelvin
Life Hours .....	36000
Wattage .....	52 Watt
Lumens .....	5200
Voltage .....	120/208/240/277
Finish .....	White
Housing .....	N/A
Mounting .....	Ceiling Grid Mount/Suspended
Lens .....	Opaque
Length .....	48 in.
Height .....	3.8 in.
Width .....	24 in.
Weight .....	14 lbs.
Warranty .....	5 Years

## PHOTOMETRICS

