



FEATURES

- Bypasses ballast to connect to 120-277 line voltage, eliminating compatibility issues
- Includes 6kV surge protection to prevent against electricity spikes
- IP64 rated, dust-tight and water resistant
- Provides an efficient replacement for 320W HID fixtures
- Emits light at an all-encompassing 360 degree beam angle
- DLC Part Number ®: PLTBA034

SKU#	Kelvin	Lumens	Base	Wattage	Voltage	DLC?	Mounting	Life Hours	Warranty
PLT-11805	4000	14,000	Mogul	100	120-277	Yes	Vertical	50,000	5 Years

ADDITIONAL PHOTOS



10.83"



FEATURES

- Direct line voltage 120-277V - Ballast Bypass
- Replaces 320W HID fixtures
- 6kV surge protection

SPECIFICATIONS

DIMMABLE	NO
DLC LISTED	YES
SAFETY RATING	UL
CRI	80
COLOR	COOL WHITE
COLOR TEMPERATURE	4000K
LIFE HOURS	50,000
WATTAGE	100 WATTS
LUMENS	14,000
VOLTAGE	120-277
FINISH.....	WHITE
HOUSING	ALUMINUM
MOUNTING	VERTICAL: BASE UP, BASE DOWN
HEIGHT	11.2 IN.
DIAMETER	5.75 IN.
WEIGHT	4.89 LBS.

TYPICAL APPLICATIONS

- Schools, Factories, Hotels
- Offices, Conference Rooms
- Hospitals

WARRANTY

Warranty

5 Years

When retrofitting HID fixtures with LED lights, ballast must be bypassed if present. If used in an enclosed fixture, the enclosed fixture must be 11.81" wide x 11.81" deep x 14.72" high (300 mm x 300 mm x 400 mm) or larger

WIRE DIAGRAM

Replacing HPS/HID Lamp

