



FEATURES

- Bypasses ballast to connect to 120-277 line voltage, eliminating compatibility issues
- Includes 6kV surge protection to prevent against electricity spikes
- IP64 rated, dust-tight and water resistant
- Provides an efficient replacement for 320W HID fixtures
- Emits light at an all-encompassing 360 degree beam angle
- DLC Part Number ®: PLTBA035

SKU#	Kelvin	Lumens	Base	Wattage	Voltage	DLC?	Mounting	Life Hours	Warranty
PLT-11611	5000	14,000	Mogul	100	120-277	Yes	Vertical	50,000	5 Years

ADDITIONAL PHOTOS



10.83"



FEATURES

- Direct line voltage 120-277V - Ballast Bypass
- Replaces 320W HID fixtures
- 6kV surge protection

TYPICAL APPLICATIONS

- Schools, Factories, Hotels
- Offices, Conference Rooms
- Hospitals

WARRANTY

Warranty

5 Years

When retrofitting HID fixtures with LED lights, ballast must be bypassed if present. If used in an enclosed fixture, the enclosed fixture must be 11.81" wide x 11.81" deep x 14.72" high (300 mm x 300 mm x 400 mm) or larger.

SPECIFICATIONS

DIMMABLE	NO
DLC LISTED	YES
SAFETY RATING	UL
CRI	80
COLOR	DAYLIGHT WHITE
COLOR TEMPERATURE	5000K
LIFE HOURS	50,000
WATTAGE	100 WATTS
LUMENS	14,000
VOLTAGE	120-277
FINISH.....	WHITE
HOUSING	ALUMINUM
MOUNTING	VERTICAL: BASE UP, BASE DOWN
LENGTH	4.84 IN.
HEIGHT	10.83 IN.
WIDTH	4.84 IN.
WEIGHT	4.89 LBS.

WIRE DIAGRAM

Replacing HPS/HID Lamp

